task

S3 EN ISO 20345: 2011 SRC

CI - HI

PRODUCT CHARACTERISTICS

- Sole injected in France
- CI-HI — Insulation against hot and cold
- Non-magnetic
- Leather upper
- Wide fit
- Offset heel

The+ PARADE TECHNOLOGIES

- PARADE AIR — Air cushioning
- DRS SYSTEM — Shock absorption in the heel
- VPS SYSTEM — Supports the arch of the foot





NON-METALLIC STITCHED EYELETS

■ 1804 BLACK | SIZE: 35 TO 48

COMPOSITION

Upper	Full-grain leather + Canvas
Linning	Fabric
Toe Cap	Polycarbonate
Stay clean insole	Fabric over EVA foam. Removable.
Puncture proof insert	Non-metallic
Sole	Two-density polyurethane
Weight for size 42*	620g * Weight per shoe

SAFETY TABLE

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole **
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe
- WRU — Water-repellent upper

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
SRA ceramic floor / Nals (soap solution)	0,32	0,37	0,28	0,34
SRB Steel / Glycerine (oil)	0,18	0,27	0,13	0,14

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update March 2020