PERFORMANCE MADE SMARTER



Universal f/I-f/f converter

4225

– Front programmable
– Input: NAMUR, NPN, PNP, Tacho, TTL & S0
– Output: Programmable bipolar mA / V, frequency or relay
– Universal power supply 21.6...253 VAC / 19.2...300 VDC


Functional highlights
- Measures frequencies up to 100 kHz.
- Active and passive current output ±23 mA / 0...23 mA.
- Buffered voltage output ±10 VDC.
- Linearization: Linear or square root function.
- 2-point process calibration.
- Programmable trigger levels -0.05…6.5 V.
- Programmable sensor supply 5…17 V.
- NAMUR sensor error detection.
- Advanced configurable input limits for increased safety.
- Digital output: NPN & PNP; 0...100 kHz with programmable logic level 5…24 V.
- Output relay with windows, setpoint and latch functionality.
- Simulation of process value during commissioning and maintenance.
- All terminals are over-voltage protected (24 VDC), polarity protected and short-circuit protected.

Technical highlights
- Accuracy < 0.06% / span.
- Temperature coefficient 0.006% / °C.
- Response time < 30 ms.
- 2.3 kVAC, 3-port galvanic isolation.
- NAMUR NE21 and NE43.

Programming
- Configuration, monitoring and diagnostics using the PR 4500 detachable communication interfaces. Product-specific functionality includes communication via Modbus and Bluetooth using our PR Process Supervisor (PPS) application, available for iOS and Android.
- All programming can be password protected.
- Scrolling help text in 7 languages.

Mounting
- Units can be mounted side by side, horizontally and vertically, without air gap on a standard DIN rail – even at 60°C ambient temperature.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order

Type	Output	
4225	1 analog output and 1 relay	: A
	2 relays	: B
	1 analog output and 1 frequency output	: C

Environmental Conditions

Operating temperature..... -20°C to +60°C
Storage temperature..... -20°C to +85°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP20

Mechanical specifications

Dimensions (HxWxD)..... 109 x 23.5 x 104 mm
Dimensions (HxWxD) w/ 4501/451x..... 109 x 23.5 x 116 / 131 mm
Weight approx..... 160 / 165 / 150 g (A / B / C)
DIN rail type..... DIN EN 60715/35 mm
Wire size..... 0.13...2.08 mm^2 AWG 26...14 stranded wire
Screw terminal torque..... 0.5 Nm

Common specifications

Supply

Supply voltage, universal..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse..... 400 mA SB / 250 VAC
Max. required power..... ≤ 2.5 W
Max. power dissipation..... ≤ 2.0 W

Isolation voltage

Test voltage..... 2.3 kVAC
Input to any (working)..... 250 VAC (reinforced)
Relay to relay (working)..... < 115 VAC (reinforced)
Relay to analog (working)..... > 115 VAC (basic)
NPN to analog (working)..... Isolated > 50 VDC
Push-Pull / PNP to analog (working)..... Shared ground with analog output

Response time

Response time (0...90%, 100...10%)..... ≤ 30 ms

Auxiliary supplies

Sensor supply limitation (terminal 44)..... 20 mA, 5…17 V

Programming..... PR 4500 communication interfaces
Signal dynamics, output..... 18 bit
Signal / noise ratio..... > 60 dB
Accuracy..... See manual for details
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span

Input specifications

Frequency input

Frequency range..... 0.001 Hz to 100 kHz
Time range, time function..... 10 µs to 999.9 s
Max. frequency / min. pulse width, with input filter ON..... 75 Hz / 8 ms

Sensor specifications

NAMUR, trig-level LOW / HIGH..... ≤ 1.2 / ≥ 2.1 mA
Tacho, trig-level LOW / HIGH..... ≤ -50 mV / ≥ +50 mV
NPN / PNP, trig-level LOW / HIGH..... ≤ 4.0 V / ≥ 7.0 V
TTL, trig-level LOW / HIGH..... ≤ 0.8 V / ≥ 2.0 V
S0, trig-level LOW / HIGH..... ≤ 2.2 mA / ≥ 9.0 mA

Special voltage / current input

User-programmable trig-levels..... -0.05...6.50 V
User-programmable trig-levels..... 0.0...10.0 mA

Output specifications

Current output

Signal range..... -23...+23 mA (bipolar)
Signal range..... 0...23 mA (unipolar)
Programmable standard ranges..... 0...20, 4...20, S4-20, ±10 mA, ±20 mA
Load (@ current output)..... ≤ 600 Ω
Load stability..... ≤ 0.001% of span / 100 Ω
Response time, programmable..... 0.0...60.0 s
Sensor error indication..... 0 / 3.5 / 23 mA / none
Current limit..... ≤ 28 mA

Buffered voltage output

Signal range..... ± 11.5 V
Programmable standard ranges..... 0…5, 1…5, 0...10, 2…10, ± 5, ± 10 VDC
Load, min..... > 2 kΩ
Response time, programmable..... 0.0...60.0 s

Relay output

Relay functions..... Setpoint, Window, Sensor error, Latch, Power and Off
Hysteresis..... 0...100%
ON and OFF delay..... 0...3600 s
Sensor error reaction..... Break / Make / Hold
Max. voltage..... 250 VAC / VDC
Max. current..... 2 A
Max. AC power..... 500 VA

Frequency output

Frequency range..... 0.001 Hz...100 kHz
Prog. pulse time (f ≤ 500 Hz)..... 1…1000 ms
Pulse time > 500 Hz..... Fixed 50%

NPN / PNP / Push-Pull output

Isink max..... 130 mA
Voltage drop 130 mA..... < 1.5 VDC
Ext. voltage (terminal 24) max..... 30 VDC
*Isource max..... 30 mA
Vout..... 24 VDC ± 10%
Voltage..... 5…24 VDC

Observed authority requirements

EMC..... 2014/30/EU & UK SI 2016/1091
LVD..... 2014/35/EU & UK SI 2016/1101
RoHS..... 2011/65/EU & UK SI 2012/3032

Approvals

c UL us, UL 508..... Pending