Specifications

Eaton 002288



Catalog Number: 002288

Eaton xEnergy Safety Ci LV systems LV switchgear. Self-tapping screw, captive

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Safety Ci screw	002288
EAN	**Product Length/Depth**
4015080022886	30 mm
Product Height	**Product Width**
10 mm	10 mm
Product Weight	**Compliances**
0.004 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

MM-CI...perforated panels
ZK-4...-CI counter circuit
M3-CI…, M-CI... mounting panels
CL mounting rails
ML-4-CI module strips
SL630-ADP-CI support angle adapter
Accessory for mounting systems
Mounting system
xEnergy Safety Ci

Special features

For mounting the installation systems directly in the lower part of the housing
Spare parts

Type

Accessory for mounting systems
Mounting system
xEnergy Safety Ci

Thread length

0 in

Features

Hardened
Accessory
Self boring

Head diameter

8 in

Thread size

Other

Fitted with:

Point

Head style

Other

Surface protection

Galvanic/electrolytic zinc plated

Accessory/spare part type

Captive screw

Resources

Brochures

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Declarations of conformity

ci_ce.pdf

2013-01-31_ci_rohs.pdf

mCAD model

ubs4_8.stp

ubs4_8.dwg

Material quality

Other

Material

Steel

Unit type

Modular system

Thread diameter

4.8 mm

Thread per inch

1

Screwing system

Pozidriv PZ

Thread type

Other

Bit size

0

Tie shape

Self-drilling

Surface treatment

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia