Specifications

Eaton 6098951

Catalog Number: 6098951

Eaton DDC DC switch disconnector, 800 A, 2 pole, 1 N/O, 1 N/C, Without rotary handle and drive shaft, rear mounting



General specifications

Product Name
Eaton DDC Insulated enclosure

Catalog Number
6098951

EAN
8711426426870

Product Length/Depth
345 mm

Product Height
160 mm

Product Width
230 mm

Product Weight
13.5 kg

Certifications
IEC/EN 60947
RoHS
VDE 0660
IEC/EN 60947-3
IEC/EN 60204
CE

Powering Business Worldwide

Features & Functions

Actuator color

Other

Actuator type

Other

Features

Version as maintenance-/service switch

Version as main switch

Functions

Optional Stop Function

Number of poles

Two-pole

General

Accessories

Auxiliary contact fitted by user.

Degree of protection

NEMA Other

Degree of protection (front side)

IP20

Lifespan, mechanical

5,000 Operations

Mounting method

Rear mounting

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

DC switch-disconnector

Main switch

Rated impulse withstand voltage (Uimp)

12000 V

Suitable for

Ground mounting

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

55 °C

Ambient storage temperature - min

-30 °C

Ambient storage temperature - max

80 °C

Terminal capacities

Terminal capacity

2 x 240 mm², solid

2 x (50 x 5) mm² , Flat conductor connection with busbars

Screw size

M12, Terminal screw

Tightening torque

28 Nm, Screw terminals

Electrical rating

Rated operational current (Ie) at DC-21B, 1000 V

800 A

Rated operational current (Ie) at DC-21B, 480 V

800 A

Rated operational current (Ie) at DC-21B, 600 V

800 A

Rated operational power at AC-23A, 400 V, 50 Hz

0 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

0 kW

Rated uninterrupted current (Iu)

800 A

Uninterrupted current

Rated uninterrupted current Iu is specified for max. cross-section.

Rated insulation voltage (Ui)

1200 V

Short-circuit rating

Rated conditional short-circuit current (Iq)

0 kA

Rated short-circuit making capacity (Icm)

54.5 kAeff

Rated short-time withstand current (Icw)

25 kA, Contacts, 1 second

25 kA

Contacts

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

1

Number of auxiliary contacts (normally open contacts)

1

Design verification

Equipment heat dissipation, current-dependent Pvid

34 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

34 W

Rated operational current for specified heat dissipation (In)

800 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

Resources

Catalogs

Eaton-industrial-switch-disconnectors-catalogue-ca008011en-en-gb.pdf

Product Range Catalog Industrial switch-disconnectors

Declarations of conformity

DA-DC-00004006.pdf

DA-DC-00003811.pdf

Drawings

eaton-rotary-switches-ddc-insulated-enclosure-dimensions-003.eps

eaton-general-mounting-p1-main-switch-symbol-002.eps

eCAD model

DA-CE-ETN.DDC-800_2-SK

Installation instructions

IL008015ZU

mCAD model

DA-CS-ddc_800_2_sk

DA-CD-ddc_800_2_sk

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia