Polyurethane spiral hoses with quick coupling and plug

Polyurethane recoils with prevoS1 safety release quick couplers



Technical characteristics

- **Max operating pressure:** 8 bar
- **Construction:** Polyurethane
- **Equipped with:** Swivel fitting
- **Temperature:** -15°C to +70°C
- **Highlight:** Excellent shape memory

ID/OD (mm)	Profile	Coupler	Max length (m)	Parts Numbers
5 x 8	European 7.4 mm	ESI 07	2	**PUS 52ES**
5 x 8	European 7.4 mm	ESI 07	4	**PUS 54ES**
6.5 x 10	European 7.4 mm	ESI 07	4	**PUS 64ES**
6.5 x 10	European 7.4 mm	ESI 07	6	**PUS 66ES**
6.5 x 10	European 7.4 mm	ESI 07	8	**PUS 68ES**
8 x 12	European 7.4 mm	ESI 07	4	**PUS 84ES**
8 x 12	European 7.4 mm	ESI 07	6	**PUS 86ES**
8 x 12	European 7.4 mm	ESI 07	8	**PUS 88ES**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.