KEWTECH

KEW2434

Earth Leakage Clamp Meter



PRODUCT DATA SHEET

- Measures 400mA/4A/100A AC current
- Resolution to 0.1mA
- Frequency selector switch to eliminate harmonics
- 28mm jaw
- Sleep feature to save batteries
- Reading Type: Averaging
- Ideal for fault finding on installations with nuisance tripping and leakage faults
- Complies to IEC61010-1 CAT. III 300V

ACCESSORIES

- Batteries
- Carry case
- Instruction Manual
- Certificate of Conformity

SPECIFICATION

AC A (50/60Hz)	400mA / 4 / 100A ±2% rdg ± 4dgt
AC V (Wide)	400mA / 4 / 100A ±2% rdg ± 4dgt [50/60Hz]±3% rdg ± 5dgt [40~400Hz]
Conductor Size	Ø28mm max.
Safety Standard	IEC61010-1 CAT.III 300V IEC61010-2-032
Effect of External Stray Magnetic Field Ø15mm 100A	20mA AC max.
Frequency Response	40~400Hz
Withstand Voltage	3700V AC for 1 minute
Effect of External Stray Magnetic Field	2mA AC approx in proximity to a 15mm-dia conductor carrying 100A AC
Withstand Voltage	3700V AC for 1 minute
Power Source	R03(AAA) (1.5V) x 2

PRODUCT INFO

- 125 x 55 x 250 Boxed (WxDxH mm)
- 0.38kg Weight
- EAN 4560187065460
- Made in Thailand

kewtechcorp.com
0345 646 1404
sales@kewtechcorp.com