Date: 11/04/2023

DPGT40.100-A 0 mbar...160 mbar 2 x G 1/4 female

Differential pressure transmitter DELTA-trans

Item number:	48687850	
Quantity:	1 pcs.	
Order code:	DPGT40.100-AN-MAM-AA4-3AJ-ZBZZ-ZZZ	4IAA-IZZZZZZ11ZZ
Overview:	DPGT40.100-A 0 mbar...160 mbar 2 x G 1/4 female bottom, in line class 2.5 Output signal: 4 ... 20 mA, 2-wire L-plug, 6 pin + earth terminal with working pressure gauge 16 bar Seperation diaphragm / sealing: FPM / FKM Window: plastic, with zero point adjustment Ingress protection: IP 65 Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number *...*	
Details:	Differential pressure transmitter DELTA-trans With integrated differential pressure and working pressure indication, Model DPGT40 Specifications according to data sheet: PV 17.19 Mounting option: 3-hole surface mounting flange at case back Differential pressure gauge: 100 mm Accuracy class for differential pressure gauge: class 2.5 Scale range: 0 mbar...160 mbar with working pressure gauge 16 bar Permissible medium temperature: -10...+90 °C Permissible ambient temperature: -10...+70 °C Ingress protection: IP 65 Measuring chamber: aluminium, black painted Process connection: 2 x G 1/4 female Connector location: bottom, in line Window: plastic, with zero point adjustment Output signal: 4 ... 20 mA, 2-wire Electrical connection: L-plug, 6 pin + earth terminal Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* serial number on dial: Serial number *...* Seperation diaphragm / sealing: FPM / FKM	

© 2023 - WIKA Instruments s.a.r.l.