BOT LIGHTING
FOR A BRIGHT FUTURE

DOWNLIGHT BODO
Adjustable downlight
BODO620
6 W - 425lm - 3000K



DIMENSIONS	A	B	C
1	46	85	



GENERAL INFORMATIONS	
Code	BODO620
Ean	8031453025823
Family	DOWNLIGHT BODO
Technology	LED
Body material	PC+AL
Diffuser / lens material	PS
Operating temperature (° C)	-20 - +40

LIGHTING DATA	
CCT (K)	3000
Luminous)ux (lm)	425
Beam (°)	36
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	6
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Hole diameter (mm)	75
Current consumption (mA)	47
Insulation class	2
Power factor	0,5
Dimmer compatibility	NO
Nominal life (h)	25000
Impact resistance (IK)	08

PACKAGING	
Packaging	BOX
Pack	20
Gross weight (Kg)	2.7
Net weight (Kg)	0.1

Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it
NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

BOT LIGHTING
FOR A BRIGHT FUTURE

DOWNLIGHT BODO

Adjustable downlight

BODO620

6W - 425lm - 3000K

- Recessed LED luminaire in thermoplastic material with integrated power supply
- Lightweight and ideal for false ceilings
- White body in thermoplastic and metal, with satin thermoplastic diffuser
- Adjustable version
- Complete with terminal for simplified wiring



Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it

NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

Release 24/1/2023