Specifications

Eaton 193170



Catalog Number: 193170

Eaton xEnergy Basic EWK small distribution board. Wall-mounted enclosure EWK complete, IP31, 288 SU, protection class II, HxWxD=950x1050x230mm

General specifications

Product Name
Eaton xEnergy Basic EWK small distribution board

Catalog Number
193170

EAN
9010238008335

Product Length/Depth
230 mm

Product Height
950 mm

Product Width
1050 mm

Product Weight
42.8 kg

Compliances
RoHS conform

Certifications
IEC/EN 62208

Powering Business Worldwide

Product specifications

Used with

EWK DBO

Basic device

Installation distribution boards

Special features

IP31 Protection Class II Steel sheet enclosure white (RAL 9016)

Type

Basic device ECO distribution board Installation distribution board

Features

EMC-version

Earthing terminal block

Neutral terminal block

Fitted with:

Locking screws can be sealed

Enclosure

Installation panel for modular installation devices

Neutral-/protective conductor terminal

Enclosure material

Steel

Built-in height

950 mm

Built-in width

1050 mm

Cable entry postion

Cable entries on top and bottom via F3A flange (not part of delivery), back plate

Terminal type

Plug-in terminals

Built-in depth

230 mm

Closure type

Other

Cover/door color

White

Cover/door model

Closed

Resources

Brochures

eaton-xenergy-basic-ewk-flyer-fl019004en-en-us.pdf

eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf

Catalogs

eaton-xcomfort-compact-distribution-catalog-ca015004en-en-us.pdf

Declarations of conformity

03_ewk-g_31_220119.pdf

DA-DC-03_EWK-G_31

Drawings

eaton-low-voltage-switch-gear-dimensions-1230dim-443.eps

Cover/door type

Door

Double

RAL-number

9016

Width in number of modular spacings

48

Ambient operating temperature details

-5 °C - 40 °C

Application

Indoor

Voltage rating at AC

400 V AC

Color

Traffic white (RAL 9016)

White

Number of rows

6

Frequency rating of contacts

50 Hz

Module rack type

Rail frame

Degree of protection

IP31

IK08 (impact resistance)

Number of module space units per row

48

Protection class

II (totally insulated)

Protective shrouding material

Plastic

Functions

Basic device

Extension possible

Material

Polystyren (plastic)

Sheet steel, powder-coated

Mounting method

Surface mounting

Surface mounted (plaster)

DIN-rail

Internal depth

128 mm

PE and N terminal number and cross section

PE: 4 x 6 x (1.5 mm² - 16 mm²)

N: 4 x 21 x (0.75 mm² - 4 mm²)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia