
MGM250-97-10-16

Mini Thermoelectric Generator Module



Parameters correct at temp.	Hot side: 250°C Cold side: 30°C	Hot side: 100°C Cold side: 30°C
Matched load output power	2.37W	0.31W
Matched load resistance	5.9Ω ± 15%	4.7Ω ± 15%
Open circuit voltage	7.8V	2.5V
Matched load output	0.6A	0.3A
Matched load output voltage	3.7V	1.2V
Heat flow through module	47W	14.2W
Maximum compress (non-destructive)		1MPa
Maximum operation temperature	Hot side - 250^{0}C. Cold side - 175^{0}C	


Geometric Dimensions


A	26mm
B	26mm
H	approx. 3.2mm


Features


- Compact structure (no moving parts)
- Reliable performance
- Maintenance-free
- Noise-free operation
- Low-carbon, green technology
- Epoxy sealed - suitable for use in high humidity conditions
- High temperature


Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com Tel: +44(0)116 279 6899 E-mail: info@etdyn.com


Matched load power output (W)
2.50
2.00
1.50
1.00
0.50
0.00
40
90
140
190
240
Hot side temperature (°C)
Tcold = 30 C
Tcold = 50 C
Tcold = 80 C
Tcold = 100 C


Matched load ouput voltage (V)
4.00
3.50
3.00
2.50
2.00
1.50
1.00
0.50
0.00
40
90
140
190
240
Hot side temperature (°C)
Tcold = 30 C
Tcold = 50 C
Tcold = 80 C
Tcold = 100 C


Matched load ouput current (A)
0.70
0.60
0.50
0.40
0.30
0.20
0.10
0.00
40
90
140
190
240
Hot side temperature (°C)
Tcold = 30 C
Tcold = 50 C
Tcold = 80 C
Tcold = 100 C


Matched load resistance (Ohm)
7.00
6.00
5.00
4.00
3.00
2.00
1.00
0.00
40
90
140
190
240
Hot side temperature (°C)
Tcold = 30 C
Tcold = 50 C
Tcold = 80 C
Tcold = 100 C


Open circuit voltage (V)
9.00
8.00
7.00
6.00
5.00
4.00
3.00
2.00
1.00
0.00
40
90
140
190
240
Hot side temperature (°C)
Tcold = 30 C
Tcold = 50 C
Tcold = 80 C
Tcold = 100 C