Brand of NTN corporation

# Technical data

## EXPAE210

Bearing units




Grey cast housing, radial insert ball bearing with eccentric locking collar, seal with slinger

## KIT CONTENT

**EX.210.G2, PAE210**

## VISUAL (S)




## PRODUCT DEFINITION

| | |
|---|---|
| **Brand** | SNR |
| **A - Housing width** | 54 mm |
| **A1 - Housing top width** | 34 mm |
| **B - Width of Inner Ring** | 49,2 mm |
| **d - Shaft diameter** | 50 mm |
| **d1 - Outer dia of eccent. Lock. collar / nut of adapter sleeve** | 67,2 mm |

| PRODUCT DEFINITION | |
|---|---|
| **E - Mounting hole thread depth** | 20 mm |
| **G - Grease fitting** | R1/8" |
| **H - Distance mounting base to centerline spheric. seating diam.** | 57,2 mm |
| **H1 - Housing foot height** | 15 mm |
| **H2 - Housing height** | 115 mm |
| **J - Mounting holes distance** | 101,6 mm |
| **L - Housing length** | 135 mm |
| **L1 - Housing foot length** | 33,5 mm |
| **N - Mounting hole dimension** | M16 |
| **S - Distance front side/bearing centre** | 24,6 mm |

| PRODUCT PERFORMANCE | |
|---|---|
| **C - Dynamic load rating** | 35100000 mN |
| **C0 - Static load rating** | 23200000 mN |
| **Operating temperature min.** | 253,15 °K |
| **Operating temperature max.** | 373,15 °K |

| OTHER FEATURES | |
|---|---|
| **Mass** | 2,71 kg |
| **Recommended tightening torque for set screw** | 11.5 N-m |