

A safety shoe with many features. Perfect for those who work in moist environments.

jalas® EXALTER 9965

EN ISO 20345:2011 S3, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR

Learn more

LOW-CUT, WATER REPELLANT WITH BOA®

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper is water repellant, perfect for those who work in moist environments. BOA® Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Double shock absorption zones
- Water repellent
- Specially designed details
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Ergonomically shaped
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- BOA® Fit System
- Soft
- Free from animal-derived materials

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION Exalter
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester
INSOLE FX3 Supreme
INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black, Red
NET WEIGHT, (SIZE 42) 1.28 kg

COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC, HRO

EAC

ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Heat-resistant outsole
- Water repellent
- Nail protection in plasma-treated composite (PTC) textile
- Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9965-34	6408487512575
35	2	3½	4	9965-35	6408487512582
36	3	4	5	9965-36	6408487512599
37	4	5	6	9965-37	6408487512605
38	5	5½	6½	9965-38	6408487512612
39	6	6½	7½	9965-39	6408487512629
40	6½	7½	8½	9965-40	6408487512636
41	7	8	9	9965-41	6408487512643
42	8	9	10	9965-42	6408487512650
43	9	9½	11	9965-43	6408487512667
44	10	10½	11½	9965-44	6408487512674
45	10½	11	12½	9965-45	6408487512681
46	11	12	13	9965-46	6408487512698
47	12	13	14	9965-47	6408487512704

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.