DATASHEET - NH FUSE 00 GG 100A 500V D.I.



Fuse-link, low voltage, 100 A, AC 500 V, NH00, gL/gG, IEC, dual indicator

Part no. NH FUSE 00 gG 100A 500V D.I.
100NHG00B

EL Number (Norway) 1664017

General specifications			
Product name			Eaton Bussmann series low voltage NH Fuse
Part no.			NH FUSE 00 gG 100A 500V D.I.
EAN			5027590428064
Product Length/Depth			79 millimetre
Product height			58 millimetre
Product width			30 millimetre
Product weight			200 gram
Compliances			CE Marked RoHS Compliant
Certifications			IEC 60269-2 DIN 43620 IEC 60269-1
Product Tradename			None
Product Type			Low voltage NH fuse
Product Sub Type			None
Electrical data			
Amperage Rating			100 A
Voltage rating			500 V
Voltage type			AC
Breaking capacity			120 kA
Class			Class gG/gL
Product specifications			
Fuse size			NH00
Insulated metal gripping lugs (IMGL)			No
Accessories			
Suitable for			EBH Size 00 to 4 Horizontal fuse switch-disconnectors Microswitch 170H0236 TD00-D Tripe pole NH Fuse base SD00-D Single pole NH Fuse base

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss13-27-14-20-05 [AFZ800020])

Fuse construction type according to IEC 60269		NH00
Voltage type		AC
Rated current	A	100
Rated voltage AC	V	500
Rated switching capacity AC	kA	120
Rated voltage DC	V	
Rated switching capacity DC	kA	
Utilization category		gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	

© 04/2023 by Eaton Industries GmbH