Specifications

Eaton 266725



Catalog Number: 266725

Eaton Moeller series NZM - Molded Case Circuit Breaker. Screw connection, 4p, 1 switch side, size 1

General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
266725

EAN
4015082667252

Product Length/Depth
75 mm

Product Height
25 mm

Product Width
75 mm

Product Weight
0.352 kg

Compliances
IEC
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM1-4, PN1-4, N(S)1-4

Type

Accessory Screw connection Terminal

Amperage Rating

160 A

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-terminals-nzm-mccb-dimensions.eps

Installation instructions

eaton-circuit-breaker-nzm1-(-4)-xka-xks-xksa-instruction-leaflet-il01219013z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm1_xks

DA-CD-nzm1_xks

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM1

Suitable for

Copper cable lugs

Four-pole

Aluminum cable lug

Number of poles

Four-pole

Model

Other

Terminal capacity (stranded cable)

12 - 2/0 AWG/kcmil (1x)

10 mm² - 70 mm² (1x)

10 mm² - 35 mm² (2x)

6 mm² - 25 mm² (2x)

10 mm² - 35 mm² (1x)

Terminal capacity (copper busbar)

Min. 12 mm x 5 mm

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia