



TEGERA® 186

Learn more

SECURE PROTECTION AGAINST MANY CHEMICALS.

A versatile chemical-resistant glove in 0.38 mm/14,9 mils thin nitrile, suitable for everything from household to chemical industry. Excellent grip due to the raised diamond pattern. Latex-free. 10 pairs/bundle. 100 bundle/carton.

CHARACTERISTICS

- High level of protection
- Durable
- Good grip

FUNCTIONS

- Approved for handling foodstuffs
- Waterproof
- Protection against chemicals
- Latex-free
- Phthalate-free
- Oil and grease resistant

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Corrosive injuries, contact with dirt, contact with chemicals, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, chemical technology work, chemical work, cleaning, foodstuff handling, laboratory work, paint spraying work, painting, paper industry work, tiling

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, food processing, pulp and paper, chemical, rubber and plastic, automotive, facilities

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves
CATEGORY Cat. III
THICKNESS 0,38 mm
LENGTH 310 mm
DEXTERITY 5
INSIDE Flock-lined
GRIP DESIGN Diamond grip pattern
COLOUR Green
PAIRS PER: BUNDLE/CARTON 10/100
AQL 0.65
DISPLAY TYPE Bag with euro slot
DIPPING MATERIAL Nitrile
INNER MATERIAL SPECIFICATION Cotton
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

CE 2777

UKCA Cat. III

EAC

TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type A
AJKLOT

EN ISO 374-5:2016

EN 388:2016+A1:2018
4101X

EN ISO 21420:2020

FEATURES

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	J	K	L	O	T
Permeation level	2	6	6	3	4	6
Degradation %	71,5	17,7	5,4	46,2	6,9	8,3

SIZE		ARTICLE NUMBER	EAN
7	S	186-7	7392626035041
8	M	186-8	7392626035058
9	L	186-9	7392626035072
10	XL	186-10	7392626035089
11	XXL	186-11	7392626035096
12	3XL	186-12	7392626037458

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.