



jalas® E-SPORT 1605

EN ISO 20345:2011 S1, P, SRC

Learn more

A light, extra comfortable safety sandal featuring high quality (S1P) protection for indoor environments. The PU-coated leather and split leather upper gives feet stability and support, and anti-static safeguard. The oil and heat-resistant PU outer sole provides excellent grip, and JALAS® aluminium toe cap protection, plasma-treated puncture protection and double impact protection zones in Ergothan® give comfort and safety.

CHARACTERISTICS

- Good shock absorption
- Light
- Excellent grip
- Perfect fit
- Extra comfortable
- Breathable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Low weight
- Reflector

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration, dry environments

SPECIFICATION

TYPE Safety footwear, Sandals
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION E-Sport
UPPER MATERIAL PU-coated leather, Split leather
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Classic
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Shock absorption zone in Ergothan
OUTSOLE MATERIAL PU outsole
FASTENING Hook-and-loop
COLOUR Black, Grey, Red
NET WEIGHT, (SIZE 42) 1.14 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2011 S1, P, SRC

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1605-36	6408487502699
37	4	5	6	1605-37	6408487502705
38	5	5½	6½	1605-38	6408487502712
39	6	6½	7½	1605-39	6408487502729
40	6½	7½	8½	1605-40	6408487502736
41	7	8	9	1605-41	6408487502743
42	8	9	10	1605-42	6408487502750
43	9	9½	11	1605-43	6408487502767
44	10	10½	11½	1605-44	6408487502774
45	10½	11	12½	1605-45	6408487502781
46	11	12	13	1605-46	6408487502798
47	12	13	14	1605-47	6408487502804

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.