Specifications

Eaton 197194

Catalog Number: 197194

Eaton DB1 Variable frequency drive, 230 V AC, 1-phase, 4.3 A, 0.75 kW, IP20/NEMA 0, Radio interference suppression filter, FS1
DB1-124D3FN-N2CC



General specifications

Product Name
Eaton DB1 Variable frequency drive

Catalog Number
197194

EAN
4015080896920

Product Length/Depth
74 mm

Product Height
130 mm

Product Width
118 mm

Product Weight
0.7 kg

Certifications
CSA
IEC/EN61800-3
RoHS, ISO 9001
RCM
UL
IEC/EN 61800-2
UL File No.: E172143
Safety: EN 61800-5-1: 2003
UL 508C
CUL
Certified by UL for use in Canada
IEC/EN 61800-3
CSA-C22.2 No. 14
UL report applies to both US and Canada
CE
UL Category Control No.: NMMS, NMMS7
IEC/EN61800-5
CSA-C22.2 No. 274
IEC/EN 61800-5-1

Powering Business Worldwide

Features & Functions

Features

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Fitted with:

PC connection

IGBT inverter

Internal DC link

Radio interference suppression filter

Additional PCB protection

General

Cable length

C2 ≤ 3 m, maximum motor cable length

C3 ≤ 10 m, maximum motor cable length

10 m, screened, maximum permissible cable length

C1 ≤ 1 m, maximum motor cable length

Communication interface

Modbus RTU

CANopen®

OP-Bus (RS485)

Connection to SmartWire-DT

No

Degree of protection

IP20

NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Frame size

FS1

Number of slots

1 (expansion)

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

MODBUS

CAN

Other bus systems

Radio interference class

C1: for conducted emissions only

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Suitable for

Branch circuits, (UL/CSA)

Ambient conditions, mechanical

Mounting position

Depending on the cooling

As required

Shock resistance

15 g, Mechanical, According to IEC/EN 60068-2-27, 11 ms

Vibration

Resistance: According to EN 61800-5-1

Climatic environmental conditions

Altitude

Max. 1000 m

Above 1000 m with 1 % derating per 100 m

Max. 2000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-10 °C

Ambient operating temperature at 150% overload - max

60 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Efficiency

96 % (η)

Heat dissipation at current/speed

31 W at 50% current and 0% speed

31.5 W at 25% current and 0% speed

36 W at 25% current and 50% speed

37 W at 100% current and 0% speed

39 W at 50% current and 50% speed

41.9 W at 100% current and 50% speed

43 W at 50% current and 90% speed

47.3 W at 100% current and 90% speed

Input current ILN at 150% overload

9.1 A

Leakage current at ground IPE - max

3.5 mA (at 230 V)

Mains switch-on frequency

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

4.3 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

4.3 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

1 HP

Apparent power

Apparent power at 230 V

0.99 kVA

Apparent power at 240 V

1.03 kVA

Maximum of one time every 30 seconds

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

U/f control

Speed control with slip compensation

BLDC motors

PM motors

Sensorless vector control (SLV)

Synchronous reluctance motors

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

230 V AC, 3-phase

240 V AC, 3-phase

Overload current IL at 150% overload

6.45 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie) at 150% overload

4.3 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

0.75 kW

Rated operational voltage

230 V AC, 1-phase

240 V AC, 1-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

15 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

Rated control voltage (Uc)

24 V DC (external, max. 100 mA)

Design verification

Equipment heat dissipation, current-dependent Pvid

60 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

4.3 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

Starting current - max

175 %, IH, max. starting current (High Overload), For 3.75 seconds every 600 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

240 VAC

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Electromagnetic compatibility (EMC)

Connecting drives to generator supplies

Brochures

eaton-powerxl-variable-frequency-drives-hvac-brochure-br040012en-en-us.pdf

eaton-powerxl-variable-frequency-drives-db1-cold-plate-brochure-br040011en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004483.pdf

DA-DC-00004467.pdf

Drawings

eaton-frequency-inverter-db1-dimensions.eps

eaton-frequency-inverter-db1-3d-drawing.eps

eCAD model

DA-CE-ETN.DB1-124D3FN-N2CC

Installation instructions

eaton-variable-frequency-drive-db1-instruction-leaflet-il040044zu.pdf

Installation videos

DX-COM-STICK3 parameter copy function

Manuals and user guides

MN040031_EN

MN040003_EN

MN040018_EN

mCAD model

DA-CS-db1_fs1

DA-CD-db1_fs1

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia