NEW

ROAD

S3S EN ISO 20345 : 2022 S3S SR FO CI HI

STANDARD VERSION 2022



■ **9834 BLACK** | 35 ▶ 48

PRODUCT CHARACTERISTICS

Non-magnetic

PARADE TECHNOLOGY EXTRAS

VPS SYSTEM — Supports the arch of the foot

DRS SYSTEM 2 — New DRS version

Be flex 2.0 — Extra-flexible sole

LIGHT, COMFORTABLE TRAINER

COMPOSITION

Upper	PU Microfibre
Lining	3D Mesh
Toe	Composite
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Non-metallic
Sole	Dual-density polyurethane
Weight size 42*	580 g *Weight per shoe

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic/Nals flooring (soap solution)	0,36	**0,36**	0,31	**0,35**
SR Ceramic + glycerine flooring	0,22	**0,24**	0,19	**0,28**

SAFETY TABLE

	Toe protection *(Safety toe cap)*
	Slip resistance *Ceramic floors + detergent*
E	Energy-absorbing heel
A	Antistatic
PS	Puncture-resistance *Non-metallic insert* *Small spike test (3.0 mm)*
SR	Slip-resistance *(ceramic flooring + oil)*
FO	Hydrocarbon resistance
CI	Sole insulation (cold)
HI	Sole insulation (heat)
WPA	Water-repellent upper

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre • Tel. +33(0) 2 41 75 32 37 • Email: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing characteristics. ©Parade, All rights reserved. Non-contractual document. Updated 03/2023