TEGERA®





TEGERA® 863R

Learn more

SUPERSOFT, DIPPED AND SUSTAINABLE

Supersoft sustainable assembly glove made of recycled polyester. Approved by GRS – Global Recycled Standard. One pair is equal to one 500 ml PET bottle. The glove is 15 gg knitted, contains also spandex and has a new Nitrile foam dipping made with reduced water usage. Touch Screen function – use your smartphone with the gloves on.

CHARACTERISTICS

- Durable
- Extra comfortable
- Good fingertip sensitivity
- Flexible
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- For touchscreen
- Thin

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with damp

PRIMARY ENVIRONMENTS OF USE

Dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Agricultural work, airport work, assembly, building and construction, construction, engineering, fine assembly, installation work, machine driving, machine operating, repair work, transport work, warehouse work

PRIMARY INDUSTRIES OF USE

Agriculture, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Heat protection gloves, Precision work gloves
CATEGORY Cat. II
LINING MATERIAL 15 gg, Recycled polyester, Spandex
LENGTH 220-260 mm
DEXTERITY 5
GRIP DESIGN Micro foam grip pattern
COLOUR Green, Grey
PAIRS PER: BUNDLE/CARTON 6/72
DISPLAY TYPE Hangtag with euro slot
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
INNER MATERIAL SPECIFICATION Recycled polyester, Elastane
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

CE Cat. II

UKCA Cat. II

EAC

TP TC 019:2011

Information/UIS

EN 407:2020 (No flame protection) X1XXXX

EN 388:2016+A1:2018 4121X

EN ISO 21420:2020

ANSI 4 ABR

Contact heat rating valid for palm area only

FEATURES

For touchscreen

SIZE		ARTICLE NUMBER	EAN
6	XS	863R-6	7340118434186
7	S	863R-7	7340118434308
8	M	863R-8	7340118434421
9	L	863R-9	7340118434544
10	XL	863R-10	7340118434667
11	XXL	863R-11	7340118434780

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.