# Product data sheet
## Characteristics

# XUM6ANXBL2
## Photoelectric sensors XU, photo electric sensor, miniature, diffuse medium, Smax=1.1 m, NPN, cable 2 m



### Main

| | |
|---|---|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | General purpose single mode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUM |
| Sensor design | Miniature |
| Detection system | Diffuse |
| Material | Plastic |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 3-wire |
| Discrete output type | NPN |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | Cable |
| Cable length | 2 m |
| Emission | Red LED diffuse |
| [Sn] nominal sensing distance | 0.8 m |

### Complementary

| | |
|---|---|
| Enclosure material | PBT |
| Lens material | PMMA |
| Maximum sensing distance | 1.1 m |
| Output type | Solid state |
| Wire insulation material | PVC |
| Status LED | Stability: 1 LED (green)<br>Output state: 1 LED (orange) |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply voltage limits | 10…30 V DC |
| Switching capacity in mA | <= 100 mA with overload and short-circuit protection |
| Switching frequency | <= 1000 Hz |
| Maximum voltage drop | <2 V |
| Current consumption | 20 mA no-load |
| Maximum delay first up | 100 ms |
| Maximum delay response | 0.5 ms |
| Maximum delay recovery | 0.5 ms |
| Setting-up | Sensitivity by potentiometer |
| Depth | 20 mm |
| Height | 33 mm |
| Width | 10 mm |
| Net weight | 0.063 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| Product certifications | CULus<br>CE<br>UKCA |
| Ambient air temperature for operation | -30…55 °C |
| Ambient air temperature for storage | -40…70 °C |
| Relative humidity | 35…95 % |
| Immunity to ambient light | 40000 Lux sunlight<br>10000 lux incandescent light |
| Vibration resistance | 9 gn, amplitude = +/- 1.5 mm (f = 10…500 Hz)for every axis conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn (duration = 11 ms) for for every axis conforming to IEC 60068-2-27 |
| IP degree of protection | IP67 conforming to IEC 60529<br>IP65 conforming to IEC 60529 |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |