Chemical protection

ULTRANEO 382

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection



CHEMICAL PROTECTION
TYPE A

EN388	EN ISO 374-1	EN ISO 374-5
2121X	TYPE A ALMNST	

EN407	CAT.CATEGORY 3	DEXTERITY
X1XXXX	0334	EN 420: 5/5

SPECIFIC ADVANTAGES

Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining

Comfort

- Extremely supple, due to the unique Mapa multi-layer process

Productivity

- Embossed texture for better grip on wet objects

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Additional benefits

- Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Laboratory tests
- Machine maintenance
- Engine part assembly
- Surface treatment
- Chemical product blending
- Handling drums of chemical products
- Manipulating valves

Edit 11/09/2023

Chemical protection

ULTRANEO 382

Frequent contact | ultra-comfort wear

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

2	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS



TYPE A

A: Methanol
L: Sulphuric acid 96%
M: Nitric acid 65%
N: Acetic acid 99%
S: Hydrofluoric acid 40%
T: Formaldehyde 37%

EN ISO 374-5 — MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Blue
Length (cm)	36
Thickness (mm)	0.95
European sizes	6 7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.5E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.2E+10 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1646 updated 02-07/10/2021
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 11/09/2023