
Angular contact ball bearings


7207-B-XL-TVP (Series 72..-B)

main dimensions to DIN 628-1, contact angle α = 40°

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	35	mm	
D	72	mm	
B	17	mm	
a	31	mm	
D_1	57,6	mm	
d_1	50,2	mm	
$D_{a\ max}$	65	mm	
$d_{a\ min}$	42	mm	
$D_{b\ max}$	67,8	mm	
$r_{1\ min}$	0,6	mm	
$r_{a1\ max}$	0,6	mm	
$r_{a\ max}$	1	mm	
r_{min}	1,1	mm	
α	40	°	Contact angle
m	0,282	kg	Mass
C_r	28000	N	Basic dynamic load rating, radial
C_{0r}	19000	N	Basic static load rating, radial
n_G	12200	1/min	Limiting speed
n_B	9600	1/min	Reference speed
C_{ur}	1280	N	Fatigue limit load, radial


a
r
r1
r
r
α
D
D1
d
d1
B


ra
ra
Da
da
Db