0402 - BALL VALVE DOUBLE FEMALE



maximum working pressure	40 bar 4 MPa 580 psi
working temperature	-20 to 80 °C -4 to 176 °F 253 to 353 °K
body	NICKEL PLATED BRASS
retaining nut	NICKEL PLATED BRASS
stem	BRASS
stem seal	NBR
'O'-rings	NBR
ball seal	NBR
handle	ZAMAK

• Convert to inch • Convert to oz • Reset Filters

Part Nb	C	E (mm)	F (mm)	F1 (mm)	H (mm)	H1 (mm)	L (mm)	L1 (mm)	M (mm)	(kg)
	All	All	All	All	All	All	All	All	All	All
0402 04 10	G1/8	8	X	14	35	29	44	25	48	.094
0402 07 10	G1/8	8	19	19	38	31	51	27	48	.165
0402 07 13	G1/4	12	19	19	38	31	53	28	48	.156
0402 10 17	G3/8	12	24	24	45	43	59	31	69	.244
0402 13 21	G1/2	15	27	27	47	44	67	34	69	.292
0402 20 27	G3/4	16.5	32	38	63	54	80	39	108	.655
0402 23 34	G1	19	41	46	67	57	94	47	108	1.036
0402 32 42	G1 1/4	21.5	55	60	97	115	112	59	180	2.467
0402 32 49	G1 1/2	22	55	60	97	115	120	62	180	2.34
0402 40 48	G2	26	70	70	104	X	122	61	190	2.614
0402 40 49	G1 1/2	22	55	55	104	X	111	55	190	2.445