Date: 24/04/2023

733.14.100 2.5 bar 2 x G 1/2 female

Differential pressure gauge, multi purpose, with diaphragm element,

Item number: 48791441

Quantity: 1 pcs.

Order code: 733.14-ZZZE-SBG325Z-AD-UZZZASZZ-ZZZZZ 7B 3GLDIZ-IZZZZZZ112ZZ
LABEL-PG1DE-ZZZZZ

Overview:
733.14.100 2.5 bar 2 x G 1/2 female
lower mount
PN 40 bar
Wetted parts: stainless-steel or NiCr-alloy (Inconel) & FPM
Case material: Stainless steel 316SS
with external zero adjustment
Ingress protection: IP 65
class 1.6
glycerine-water-mixture
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Pressure Gauge Standard: International (standard Europe)
stop-pin at 6 o'clock
WIKA Serial number *...*
Label: WIKA standard without / with Tag-number

Details:
Differential pressure gauge, multi purpose, with diaphragm element,
high overpressure limit
Model: 733.14
Specifications according to data sheet: PM 07.13
Case: stainless steel
Bezel ring: stainless steel
Movement: stainless steel
Wetted parts: stainless-steel or NiCr-alloy (Inconel) & FPM
Case filling: with
Nominal size: 100 mm
Overpressure safety/working pressure max.: PN 40 bar
Scale range: 0...2.5 bar
Process connection: 2 x G 1/2 female
Connector location: lower mount
Permissible ambient temperature: -20...+60 °C
Permissible medium temperature: -20...+100 °C
Accuracy class: class 1.6
Case filling fluid: glycerine-water-mixture
Case material: Stainless steel 316SS
Case surface: bare
Ingress protection: IP 65

© 2023 - WIKA Instruments s.a.r.l.

Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*
stop pin on dial: at 6 o'clock
with external zero adjustment

© 2023 - WIKA Instruments s.a.r.l.