Switch Enclosures

Switch Modules

Neon Modules

Data/Telecom Enclosures Euro Format

Euro Data Modules

IP66



K56420GRY



K56421WHI



K56422BLK



K56422GRY

10 AMP



56881BLK



56882BLK



56883BLK

20 AMP



56891BLK



56892BLK



56893BLK



56896BLK



56889RED

IP66



K56423GRY



K56423WHI



K56423BLK

TELECOM



K5820WHI K5820BLK



K5821WHI K5821BLK

K56420GRY 1
K56420WHI 1
K56420BLK 1

1 GANG FOR USE WITH ANY ONE SWITCH MODULE

K56421GRY 1
K56421WHI 1
K56421BLK 1

1 GANG WITH NEON FOR USE WITH ANY SWITCH AND ANY NEON MODULE

K56422GRY 1
K56422WHI 1
K56422BLK 1

2 GANG FOR USE WITH ANY TWO SWITCH MODULES

Fixing holes are for No.8 woodscrews (not supplied).

Each enclosure is fitted with a neon which should be wired as a locator.

The enclosure has 4 x 20mm entries, 1 on top, bottom and each side and is supplied with an earth terminal and a loop terminal in the back box.

NOTE: These enclosures are for use with the Masterseal Plus™ switch and neon modules.

DIMENSIONS:
95 x 95 x 57mm

IP66 to BS EN 60529: 1992

56881BLK 10
10A SP
ONE-WAY

56882BLK 10
10A SP
TWO-WAY

56883BLK 10
10A DP
ONE-WAY

For use only with Masterseal Plus™ switch enclosures.

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

56891BLK 10
20A SP
ONE-WAY

56892BLK 10
20A SP
TWO-WAY

56893BLK 10
20A
INTERMEDIATE

56896BLK 10
20A DP
ONE-WAY

For use only with Masterseal Plus™ switch enclosures.

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

56889RED 10
200-250V NEON
RED

BS 5733: 2010

K56423GRY 1
K56423WHI 1
K56423BLK 1

1 GANG
DATA ENCLOSURE
FOR 2 MODULE EURO OUTLET
HALF MODULE BLANKS SOLD SEPARATELY

2 data modules can be accommodated providing care is used to ensure that the cables are correctly routed through the outlet.

Fixing holes are for No.8 woodscrews (not supplied). Backbox has 4 x 20mm entries, 1 on each edge. Supplied with an earth terminal and a loop terminal in the backbox.

DIMENSIONS:
160 x 117 x 89mm

IP66 to BS EN 60529: 1992

K5820WHI 5
K5820BLK 5

K5821WHI 5
K5821BLK 5

TELEPHONE SECONDARY
ONE MODULE

DIMENSIONS:
25 x 50mm

BS 6312 Pt.2

See Logic Plus page 54 for a full range of Euro modules