Date: 11/04/2023

PSD-4; -1...+3 bar gauge ; two switching output (PNP/NPN) + 4...20 mA

PSD-4; -1...+3 bar gauge ; two switching output (PNP/NPN) + 4...20 mA

Item number:	58455565	
Quantity:	1 pcs.	
Order code:	PSD-4-CZ-BV340-NDZZ-WW-ZZ	W1011PS4Z-SZAB-P-GSFI
Overview:	PSD-4; -1...+3 bar gauge ; two switching output (PNP/NPN) + 4...20 mA Electronic pressure switch with display Output signal: two switching output (PNP/NPN) + 4...20 mA IO-Link: without Power supply: 15...35 V DC Measuring range: -1...+3 bar gauge Process connection: 1/2 NPT Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (5-pin) pin assignment el. connection: U+=1, U-=3, S+=5, SP1=4, SP2=2 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86	
Details:	PSD-4; -1...+3 bar gauge ; two switching output (PNP/NPN) + 4...20 mA Electronic pressure switch with display Output signal: two switching output (PNP/NPN) + 4...20 mA IO-Link: without Power supply: 15...35 V DC Measuring range: -1...+3 bar gauge Process connection: 1/2 NPT Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (5-pin) pin assignment el. connection: U+=1, U-=3, S+=5, SP1=4, SP2=2 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86	

© 2023 - WIKA Instruments s.a.r.l.