Daikin AC Domestic units to KNX Interface with binary inputs

Item number: INKNXDAI001I100

The Daikin-KNX interface allows full bidirectional communication between Daikin AC Domestic units and KNX installations. It has four potential-free binary inputs available to integrate and configure external devices (window contacts or presence detectors) to improve energy efficiency.



Daikin to KNX - 1 indoor unit

Features and benefits

- **ETS configuration**
  The interface is configured using the ETS standard configuration tool software.
- **Multiple energy efficiency functions available**
  Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.
- **Total unit control and monitoring from KNX**
  Through internal variables, running hours counter (for maintenance purposes), and error indication.
- **AC unit control by both remote controller and KNX**
  The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.
- **Compatible with all KNX thermostats in the market**
  All the required DPT objects to be compatible with all KNX thermostats in the market are available.
- **Smooth KNX thermostat integration**
  KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.
- **Up to five scenes saved/executed from KNX**
  Up to five scenes can be saved and executed from KNX.
- **Compact dimensions, allowing inside installation**
  The interface can be quickly installed inside the AC unit thanks to its reduced dimensions.

Daikin AC Domestic units to KNX Interface with binary inputs



General

Net Width (mm)	88
Net Height (mm)	56
Net Depth (mm)	90
Net Weight (g)	80
Packed Width (mm)	8
Packed Height (mm)	7
Packed Depth (mm)	12
Packed Weight (g)	100
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	0.232
Input Voltage (V)	29 VDC
Power Connector	2-pole
Configuration	ETS
Capacity	1 Indoor unit.
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Daikin Residential

Daikin AC Domestic units to KNX Interface with binary inputs



General

Content of Delivery	Intesis Gateway, Installation Manual, AC Connection cable.
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INKNXDAI001I100
Country of Origin	Spain
HS Code	8517620000
Export Control Classification Number (ECCN)	EAR99


Physical Features

Connectors / Input / Output	KNX, HVAC port, Binary inputs (dry contact).
LED Indicators	KNX

Certifications and Standards

ETIM Classification	EC001604
WEEE Category	IT and telecommunications equipment

Use Case



Integration example.