Technical Specifications

FALCON OFFSHORE

Description:



Miller Falcon self-retracting OFFSHORE lifelines is the safest & most robust range of composite retractable lifelines for offshore environments.
This range is supplied with a stainless steel swivel at the top and a stainless steel swivel snap hook at the bottom of the cable.

- High quality, corrosion-resistant components (Extend service life)
- No annual factory re-certification required
  (Lowers cost, increases productivity)
- Lightweight, robust composite unit
  (Facilitates handling and transport)
- Unique side payout design (Reduces wear on the entry guide & cable)
- Highly visible load indicator at the snap hook (Enhanced safety)
- Quick-activating braking mechanism (Arrest a fall within centimetres)
- Dual swivels (Prevent damage to the lifeline)
- Built-in, moulded handle on 15 & 20m

References: 1028680-1028681-1028682-1028683

Features:

Housing : high impact nylon
Hub: heat treated aluminium
Braking mechanism : stainless steel and bronze
Main Spring : stainless steel SS 301
Cable lifeline : 4,5mm stainless steel grade SS 304
Snap hook with FI : stainless steel grade SS 420
double-locking swivel snap hook with 22mm opening
Breaking strength: > 1200 daN
Certified to EN 360
Temperature: -30°C to +50°C



The cable is now supplied with double ferrule

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com

Réf	Lenght by m	Cable	Connexion				Weight Kg	Dimensions by mm
			Top		Cable			
			Karabiner	Swivel	Swivel	FI Stainless Steel		
1028680	6,2	Stainless Steel		X	X	X	4	255 x 213 x 101
1028681	10	Stainless Steel		X	X	X	5	255 x 213 x 101
1028682	15	Stainless Steel		X	X	X	6,7	342 x 246 x 101
1028683	20	Stainless Steel		X	X	X	7,6	342 x 246 x 101

* Approved for horizontal application when used with a CS20 karabiner & a 1m steel anchorage sling.

**The CE standard requires inspection by a trained end-user competent person, following the Miller Repair

IN CASE OF OFFSHORE /HARSH ENVIRONMENT APPLICATION WE RECOMMEND TO MAKE MORE OFTEN ANNAUL INSPENTIONS.

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com