finder®
SWITCH TO THE FUTURE

Energy meters

7E
SERIES

- Panels for electrical distribution
- Control panels
- Electrical energy control
- Industrial robots
- Road / tunnel lighting
- Elevators and lifts



FINDER reserves the right to alter characteristics at any time without notice. FINDER assumes no liability for damage to persons or property, caused as a result of the incorrect use or application of its products.




kWh Energy meter 1-phase with electro-mechanical display and SO pulse output

Type 7E.12.8.230.0002
10 (25) A , kWh, No MID, horizontal display

Type 7E.13.8.230.0010
5 (32) A , kWh, MID, 1 module wide

Type 7E.16.8.230.0010
10 (65) A, kWh, MID, horizontal display

- Complies with EN 62053-21 and EN 50470
- Certified by PTB (7E.13 and 7E.16) (Physikalisch - Technischen Bundesanstalt)
- Accuracy class 1/B
- Protection class II
- SO pulse output for remote energy monitoring according to EN 62053-31
- Tamper-proof cover with lead seal facility available as an accessory
- Space saving small size
- 35 mm rail (EN 60715) mount

	7E.12.8.230.0002	7E.13.8.230.0010	7E.16.8.230.0010
			
	• Nominal current 10 A (25 A Maximum) • 1-phase 230 V AC • SO pulse output • 35 mm wide	• Nominal current 5 A (32 A Maximum) • MID certified (50 Hz) • 1-phase 230 V AC • SO pulse output • 17.5 mm wide	• Nominal current 10 A (65 A Maximum) • MID certified (50 Hz) • 1-phase 230 V AC • SO pulse output • 35 mm wide
			

For outline drawing see page 15

Specification				
Nominal/Maximum current	A	10/25	5/32	10/65
Minimum measured current	A	0.04	0.02	0.04
Current range (within accuracy class)	A	0.5…25	0.25…32	0.5…65
Maximum peak current	A	750 (10 ms)	960 (10 ms)	1950 (10 ms)
Supply (& monitored) voltage (U_N)	V AC	230	230	230
Operating range		(0.8…1.15)U_N	(0.8…1.15)U_N	(0.8…1.15)U_N
Frequency	Hz	50	50	50
Power consumption	W	< 0.5	< 0.4	< 0.5
Display (digit height 4 mm)		Six digit counter, red decimal digit	Seven digit counter, red decimal digit	
Max. totalising count/Min. increment	kWh	99 999.9/0.1	999 999.9/0.1	999 999.9/0.1
LED-Pulses per kWh		2000	2000	1000
Open collector- output specification (SO+/SO–)				
Voltage (external supply)	V DC	5…30	5…30	5…30
Maximum current	mA	20	20	20
Maximum leakage current @ 30 V/25 °C	µA	10	10	10
Pulses per kWh		1000	1000	1000
Pulse length	ms	50	50	50
Internal series resistance	Ω	100	100	100
Maximum cable length @ 30 V/20 mA	m	1000	1000	1000
Technical data				
Accuracy class		1	B	B
Ambient temperature (Within accuracy class)	°C	–10…+55	–10…+55	–10…+55
Protective class		II	II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	CE PTB	

kWh Energy meter 3-phase
MID with electromechanical display and SO pulse output

Type 7E.36.8.400.0010
10 (65) A, kWh, MID


Type 7E.36.8.400.0012
10 (65) A, kWh, dual tariff, MID

- Complies with EN 62053-21 and EN 50470
- Certified by PTB (Physikalisch - Technischen Bundesanstalt)
- Accuracy class B
- Protection class II
- SO pulse output for remote energy monitoring according to EN 62053-31
- Tamper-proof cover with lead seal facility available as an accessory
- 35 mm rail (EN 60715) mount

7E.36.8.400.0010



- Nominal current 10 A (65 A Maximum)
- MID certified (50 Hz)
- 3-phase
- SO pulse output
- 70 mm wide




7E.36.8.400.0012



- Nominal current 10 A (65 A Maximum)
- MID certified (50 Hz)
- 3-phase
- SO pulse output
- Dual tariff (Day and Night)
- 70 mm wide

$R_{T1,T2}$ = Tariff switching equipment



For outline drawing see page 15

Specification			
Nominal/Maximum current	A	10/65	10/65
Minimum measured current	A	0.04	0.04
Current range (within accuracy class)	A	0.5…65	0.5…65
Maximum peak current	A	1950 (10 ms)	1950 (10 ms)
Supply (& monitored) voltage (U_N)	V AC	3 x 230	3 x 230
Operating range		(0.8…1.15)U_N	(0.8…1.15)U_N
Frequency	Hz	50	50
Power consumption per phase	W	< 1.5	< 1.5
Display (digit height 4 mm)		Seven digit counter, red decimal digit	
Max. totalising count/Min. increment	kWh	999 999.9/0.1	999 999.9/0.1
LED-Pulses per kWh		100	100
Open collector- output specification (SO+/SO–)			
Voltage (external supply)	V DC	5…30	5…30
Maximum current	mA	20	20
Maximum leakage current @ 30 V/25 °C	µA	10	10
Pulses per kWh		100	100
Pulse length	ms	50	50
Internal series resistance	Ω	100	100
Maximum cable length @ 30 V/20 mA	m	1000	1000
Technical data			
Accuracy class		B	B
Ambient temperature	°C	–10…+55	–10…+55
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE PTB	

V-2018, www.findernet.com

Single-phase

Single-phase Bi-directional energy meters with backlit LCD display

Type 7E.64.8.230.0001
kWh, kW, V

- Display of active energy consumption (kWh)
- Scroll to view instantaneous voltage (V) and active power (kW)
- 7 digit backlit LCD display
- Class 1 accuracy according to EN 62053-21
- SO output for remote energy monitoring according to EN 62053-31. Active energy (kWh) only

Type 7E.64.8.230.0010
Multifunction MID certified


- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- 7 digit backlit LCD display
- Active power accuracy Class B according to EN 50470-3
- Programmable* SO pulse output for remote energy monitoring according to EN 62053-31
- Accessories: sealable tamperproof terminal cover
- Protection category II
- 35 mm rail (EN 60715) mount

* SO output can be associated with kWh, kVAh or kvarh.

NEW **7E.64.8.230.0001**




- Reference current 5 A (40 A Maximum)
- 1-phase 230 V AC
- kWh + instantaneous voltage & kW, V



NEW **7E.64.8.230.0010**



- Reference current 5 A (40 A Maximum)
- 1-phase 230 V AC
- kWh, kVAh or kvarh + instantaneous V, A, PF, kW, kVA, kvar & Hz
- MID certified



For outline drawing see page 15

Specification			
Reference/Maximum current I_n/I_{max}	A	5/40	5/40
Starting current I_{st}	A	0.02	0.02
Minimum measured current I_{min}	A	0.25	0.25
Current range (within accuracy class)	A	0.5…40	0.5…40
Maximum peak current	A	1200 (10 ms)	1200 (10 ms)
Supply (& monitored) voltage U_N	V AC	230	230
Operating range		$(0.8…1.2)U_N$	$(0.8…1.2)U_N$
Frequency	Hz	50/60	50/60
Power consumption	W/VA	≤ 0.5/1.5	≤ 0.5/1.5
Display		Seven digit counter - backlit LCD display	
Max. totalising count/Min. increment	kWh	999 999.9/0.1	999 999.9/0.1
LED pulses per kWh		5000	5000
LED pulse length	ms	4±0.5	4±0.5
Output specification (SO+/SO–)			
Number/Type		1 opto-isolated output	1 opto-isolated output
Voltage range/Maximum current (conforming to EN 62053-1)	V DC/mA	3.3…27/1…27	3.3…27/1…27
Pulses per kWh*	Imp/kWh*	1000	1000
Pulse length	ms	100 ± 0.5	100 ± 0.5
Maximum cable length	m	1000	1000
Technical data			
Accuracy class EN 62053-21 (non MID)/ EN 50470-3 (MID)		1	B
Ambient temperature (Within accuracy class)	°C	–25…+55	–25…+55
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	

Three-phase

Multifunction Dual tariff energy meters Bi-directional, MID certified, two SO outputs with backlit LCD display for 3 or 4 wire systems Infra-red communications port

Type 7E.78.8.400.0112
Direct connection up to 80 A, dual tariff

Type 7E.86.8.400.0112
6 A direct connection, up to 50 000 A using current transformer, dual tariff

- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh - for both T1 and T2 tariffs - for the total system or per phase
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- Fault indication in the event of loss or incorrect phase sequence
- 8 digit backlit LCD display
- Active power accuracy Class B according to EN 50470-3
- Reactive power acurracy Class 2 according to EN 62053-23
- Two programmable** SO pulse outputs for remote energy monitoring according to EN 62053-31
- Infra-red communications port for data exchange with various field protocols, using optional modules
- Protection category II
- Accessories: sealable tamperproof terminal cover
- 35 mm rail (EN 60715) mount

* Minimum CT ratio: 1:1
Maximum CT ratio: 10 000:1
CT full scale programmable: 1 or 5 A
** SO output can be associated with kWh, kVAh or kvarh.

For outline drawing see page 15

NEW **7E.78.8.400.0112**




- Reference current 5 A (80 A Maximum)
- Three-phase systems - 3 or 4 wire
- Dual tariff
- MID certified


NEW **7E.86.8.400.0112**



- Reference current 1 A (6 A Maximum)
- Three-phase systems - 3 or 4 wire
- Usable with current transformer*
- Programmable CT secondary*
- Dual tariff
- MID certified



$R_{T1,T2}$ = Tariff switching equipment



$R_{T1,T2}$ = Tariff switching equipment

Specification			
Reference/Maximum current I_n/I_{max}	A	5/80	1/6
Starting current I_{st}	A	0.02	0.002
Minimum measured current I_{min}	A	0.25	0.01
Current range (within accuracy class)	A	0.5…80	0.05…6
Maximum peak current	A	2400 (10 ms)	120 (500 ms)
Supply (& monitored) voltage U_N	V AC	3 x 230/400…3 x 240/415	3 x 230/400…3 x 240/415
Operating range		$(0.8…1.2)U_N$	$(0.8…1.2)U_N$
Frequency	Hz	50/60	50/60
Power consumption per phase	W/VA	≤ 0.5/7.5	≤ 0.5/7.5
CT burden (per phase)	VA	—	0.04
Display		Eight digit counter - backlit LCD display	
Max. totalising count/Min. increment	kWh	999 999.99/0.01	999 999.99/0.01
LED pulses per kWh		1000	10 000
LED pulse length	ms	10±0.5	10±0.5
Output specification (SO+/SO–)			
Number/Type		2 opto-isolated outputs	2 opto-isolated outputs
Maximum values (conforming to EN 62053-31)	V AC-DC/mA	250/100	250/100
Pulses per kWh**	Imp/kWh**	100	See table page 13
Pulse length	ms	50 ± 2	50 ± 2
Maximum cable length (30 V/20 mA)	m	1000	1000
Tariff input - opto-isolated			
Voltage range	V AC/DC	80…275	80…275
Technical data			
Accuracy class EN 50470-3 (MID)		B	B
Ambient temperature	°C	–25…+55 °C	–25…+55 °C
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	

V-2018, www.findernet.com

Single-phase

Multifunction, Bi-directional energy meter MID certified with RS485 Modbus integrated interface and backlit LCD display


- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- 7 digit backlit LCD display
- Active power accuracy Class B according to EN 50470-3
- RS485 Modbus integrated communications port
- Programmable** SO pulse output for remote energy monitoring according to EN 62053-31
- Accessories: sealable tamperproof terminal cover
- Protection category II
- 35 mm rail (EN 60715) mount

* Default transmission baud rate: 19 200 bps
** SO output can be associated with kWh, kVAh or kvarh.

NEW **7E.64.8.230.0210**



- Reference current 5 A (40 A Maximum)
- RS485 Modbus integrated interface
- 1-phase 230 V 50/60 Hz
- MID certified



For outline drawing see page 16

Specification		
Reference/Maximum current I_n/I_{max}	A	5/40
Starting current I_{st}	A	0.02
Minimum measured current I_{min}	A	0.25
Current range (within accuracy class)	A	0.5…40
Maximum peak current	A	1200 (10 ms)
Supply (& monitored) voltage U_N	V AC	230
Operating range		$(0.8…1.2)U_N$
Frequency	Hz	50/60
Power consumption	W/VA	≤ 0.5/1.5
Display		Seven digit counter - backlit LCD display
Max. totalising count/Min. increment	kWh	999 999.9/0.1
LED pulses per kWh		5000
LED pulse length	ms	4±0.5
Modbus technical data		
Bus System		RS485 Modbus
Conforms to standard		EIA RS485
Max. bus length	m	1000
Max. Modbus energy meters connectable		32
Baud rate*	Baud	2400, 4800, 9600, 19 200, 38 400
Output specification (SO+/SO–)		
Number/Type		1 opto-isolated output
Voltage range/Maximum current (conforming to EN 62053-31)	V DC/mA	3.3…27/1…27
Pulses per kWh**	Imp/kWh**	1000
Pulse length	ms	100 ± 2
Technical data		
Accuracy class		B
Ambient temperature (Within accuracy class)	°C	–25…+55
Protective class		II
Protection category: Housing/terminals		IP 50/IP 20
Approvals (according to type)		CE

Note regarding energy meters with Modbus interface (Types 7E.64.8.230.0210, 7E.78.8.400.0212 and 7E.86.8.400.0212):

The energy meter's Modbus protocol contains pre-configured information.
Should you need to change any parameter - use the configuration software.
The configuration software can be found at www.findernet.com

Three-phase

Multifunction Dual tariff energy meters Bi-directional, MID certified with RS485 Modbus integrated interface, single SO output and backlit LCD display for 4 wire systems

Type 7E.78.8.400.0212
Direct connection up to 80 A, dual tariff

Type 7E.86.8.400.0212
6 A direct connection, up to 50 000 A using current transformer, dual tariff

- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh - for both T1 and T2 tariffs - for the total system or per phase
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- Fault indication in the event of loss or incorrect phase sequence
- 8 digit backlit LCD display
- RS485 Modbus integrated communications port
- Programmable*** SO pulse output for remote energy monitoring according to EN 62053-31
- Active power accuracy Class B according to EN 50470-3
- Reactive power accuracy Class 2 according to EN 62053-23
- Protection category II
- Accessories: sealable tamperproof terminal cover
- 35 mm rail (EN 60715) mount

* Minimum CT ratio: 1:1
Maximum CT ratio: 10 000:1
CT secondary programmable: 1 or 5 A
** Default transmission baud rate: 19 200 bps
*** SO output can be associated with kWh, kVAh or kvarh.

For outline drawing see page 16

NEW **7E.78.8.400.0212**




- Reference current 5 A (80 A Maximum)
- RS485 Modbus integrated interface
- Three-phase systems - 4 wire
- Dual tariff
- MID certified


NEW **7E.86.8.400.0212**



- Reference current 1 A (6 A Maximum)
- RS485 Modbus integrated interface
- Three-phase systems - 4 wire
- Usable with current transformer*
- Programmable CT secondary*
- Dual tariff
- MID certified



$R_{T1,T2}$ = Tariff switching equipment



$R_{T1,T2}$ = Tariff switching equipment

Specification			
Reference/Maximum current I_n/I_{max}	A	5/80	1/6
Starting current I_{st}	A	0.02	0.002
Minimum measured current I_{min}	A	0.25	0.01
Current range (within accuracy class)	A	0.5…80	0.05…6
Maximum peak current	A	2400 (10 ms)	120 (500 ms)
Supply (& monitored) voltage U_N	V AC	3 x 230/400…3 x 240/415	3 x 230/400…3 x 240/415
Operating range		(0.8…1.2)U_N	(0.8…1.2)U_N
Frequency	Hz	50/60	50/60
Power consumption per phase	W/VA	≤ 1/3.5	≤ 1/3.5
CT burden (per phase)	VA	—	0.04
Display		Eight digit counter - backlit LCD display	
Max. totalising count/Min. increment	kWh	999 999.99/0.01	999 999.99/0.01
LED pulses per kWh		1000	10 000
LED pulse length	ms	10±0.5	10±0.5
Modbus technical data			
Bus system		RS485 Modbus	RS485 Modbus
Conforms to standard		EIA RS485	EIA RS485
Max. bus length	m	1000	1000
Max. Modbus energy meters connectable		32	32
Baud rate**	Baud	300…57 600	300…57 600
Output specification (SO+/SO–)			
Number/Type		1 opto-isolated output	1 opto-isolated output
Voltage range/Maximum current (conforming to EN 62053-31)	V DC/mA	3.3…27/1…27	3.3…27/1…27
Pulse per kWh***	Imp/kWh***	100	See table page 13
Pulse length	ms	50 ± 2	50 ± 2
Tariff input - opto-isolated			
Voltage range	V AC/DC	80…275	80…275
Technical data			
Accuracy class		B	B
Ambient temperature (Within accuracy class)	°C	–25…+55	–25…+55
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	

V-2018, www.findernet.com

Single-phase

Multifunction energy meter
Bi-directional, MID certified with M-Bus integrated interface and backlit LCD display


- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- 7 digit backlit LCD display
- Active power accuracy Class B according to EN 50470-3
- M-Bus integrated communications port
- Programmable** SO pulse output for remote energy monitoring according to EN 62053-31
- Accessories: sealable tamperproof terminal cover
- Protection category II
- 35 mm rail (EN 60715) mount

* Default transmission baud rate: 2400 bps
** SO output can be associated with kWh, kVAh or kvarh.

NEW **7E.64.8.230.0310**



- Reference current 5 A (40 A Maximum)
- M-Bus integrated interface
- 1-phase 230 V 50/60 Hz
- MID certified



For outline drawing see page 16

Specification		
Reference/Maximum current I_n/I_{max}	A	5/40
Starting current I_{st}	A	0.02
Minimum measured current I_{min}	A	0.25
Current range (within accuracy class)	A	0.5…40
Maximum peak current	A	1200 (10 ms)
Supply (& monitored) voltage U_N	V AC	230
Operating range		$(0.8…1.2)U_N$
Frequency	Hz	50/60
Power consumption per phase	W/VA	≤ 0.5/1.5
Display		Seven digit counter - backlit LCD display
Max. totalising count/Min. increment	kWh	999 999.9/0.1
LED pulses per kWh		5000
LED pulse length	ms	4±0.5
M-bus technical data		
Bus System		M-Bus
Conforms to standard		EN 13757-1-2-3
Baud rate*	Baud	300, 2400, 9600
Output specification (SO+/SO–)		
Number/Type		1 opto-isolated output
Voltage range/Maximum current (conforming to EN 62053-31)	V DC/mA	3.3…27/1…27
Pulses per kWh**	Imp/kWh**	1000
Pulse length	ms	100 ± 0.5
Technical data		
Accuracy class		B
Ambient temperature (Within accuracy class)	°C	–25…+55
Protective class		II
Protection category: Housing/terminals		IP 50/IP 20
Approvals (according to type)		CE

Note regarding energy meters with M-Bus interface (Types 7E.64.8.230.0310, 7E.78.8.400.0312 and 7E.86.8.400.0312):

The energy meter's M-Bus protocol contains pre-configured information.
Should you need to change any parameter - use the configuration software.
The configuration software can be found at www.findernet.com

Three-phase

Multifunction Dual tariff energy meters Bi-directional, MID certified with M-Bus integrated interface, single SO output and backlit LCD display for 3 or 4 wire systems

Type 7E.78.8.400.0312
Direct connection up to 80 A, dual tariff

Type 7E.86.8.400.0312
6 A direct connection, up to 50 000 A using current transformer, dual tariff

- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh - for both T1 and T2 tariffs - for the total system or per phase
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- Fault indication in the event of loss or incorrect phase sequence
- 8 digit backlit LCD display
- M-Bus integrated communications port
- Programmable*** SO pulse output for remote energy monitoring according to EN 62053-31
- Active power accuracy Class B according to EN 50470-3
- Reactive power accuracy Class 2 according to EN 62053-23
- Protection category II
- Accessories: sealable tamperproof terminal cover
- 35 mm rail (EN 60715) mount

* Minimum CT ratio: 1:1
Maximum CT ratio: 10 000:1
CT secondary programmable: 1 or 5 A
** Default transmission baud rate: 2400 bps
*** SO output can be associate with kWh, kVAh or kvarh.

NEW **7E.78.8.400.0312**





- Reference current 5 A (80 A Maximum)
- M-Bus integrated interface
- Three-phase systems programmable 3 or 4 wire
- Dual tariff
- MID certified

NEW **7E.86.8.400.0312**



- Reference current 1 A (6 A Maximum)
- M-Bus integrated interface
- Three-phase systems programmable 3 or 4 wire
- Usable with current transformer*
- Programmable CT secondary*
- Dual tariff
- MID certified





For outline drawing see page 16

Specification			
Reference/Maximum current I_n/I_{max}	A	5/80	1/6
Starting current I_{st}	A	0.02	0.002
Minimum measured current I_{min}	A	0.25	0.01
Current range (within accuracy class)	A	0.5…80	0.05…6
Maximum peak current	A	2400 (10 ms)	120 (500 ms)
Supply (& monitored) voltage U_N	V AC	3 x 230/400…3 x 240/415	3 x 230/400…3 x 240/415
Operating range		$(0.8…1.2)U_N$	$(0.8…1.2)U_N$
Frequency	Hz	50/60	50/60
Power consumption per phase	W/VA	≤ 0.5/7.5	≤ 0.5/7.5
CT burden (per phase)	VA	—	0.04
Display		Eight digit counter - backlit LCD display	
Max. totalising count/Min. increment	kWh	999 999.99/0.01	999 999.99/0.01
LED pulses per kWh		1000	10 000
LED pulse length	ms	10±0.5	10±0.5
M-bus technical data			
Bus system		M-Bus	M-Bus
Conforms to standard		EN 13757-1-2-3	EN 13757-1-2-3
Baud rate**	Baud	300…9600	300…9600
Output specification (SO+/SO–)			
Number/Type		1 opto-isolated output	1 opto-isolated output
Voltage range/Maximum current (conforming to EN 62053-31)	V DC/mA	3.3…27/1…27	3.3…27/1…27
Pulses per kWh***	Imp/kWh***	100	See table page 13
Pulse length	ms	50 ± 2	50 ± 2
Tariff input - opto-isolated			
Voltage range	V AC/DC	80…275	80…275
Technical data			
Accuracy class		B	B
Ambient temperature (Within accuracy class)	°C	–25…+55	–25…+55
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	

V-2018, www.findernet.com

Three-phase

Multifunction energy meter
Bi-directional, MID certified with Ethernet Modbus TCP integrated interface and backlit LCD display for 4 wire systems

Type 7E.78.8.400.0410:
Direct connection up to 80 A

Type 7E.86.8.400.0410:
6 A direct installation, up to 50 000 A using current transformer

- Display of total or partial (resettable) energy consumption: kWh, kVAh or kvarh - for the total system or per phase
- Scroll to view the following instantaneous values: V, A, PF, kW, kVA, kvar, Hz and direction of power flow
- Fault indication in the event of loss or incorrect phase sequence
- 8 digit backlit LCD display
- Ethernet Modbus TCP integrated communications port
- Programmable** SO pulse output for remote energy monitoring according to EN 62053-31
- Active power accuracy Class B according to EN 50470-3
- Reactive power accuracy Class 2 according to EN 62053-23
- Protection category II
- Accessories: sealable terminal cover tamper
- 35 mm rail (EN 60715) mount

* Minimum CT ratio: 1:1
Maximum CT ratio: 10 000:1
CT secondary programmable: 1 or 5 A


** SO output can be associate with kWh, kVAh or kvarh.

For outline drawing see page 16

NEW **7E.78.8.400.0410**




- Reference current 5 A (80 A Maximum)
- Ethernet Modbus TCP integrated interface
- Three-phase systems - 4 wire



NEW **7E.86.8.400.0410**



- Reference current 1 A (6 A Maximum)
- Ethernet Modbus TCP integrated interface
- Three-phase systems - 4 wire
- Usable with current transformer*
- Full scale (FSA) programmable*



Specification			
Reference/Maximum current I_n/I_{max}	A	5/80	1/6
Starting current I_{st}	A	0.02	0.002
Minimum measured current I_{min}	A	0.25	0.01
Current range (within accuracy class)	A	0.5…80	0.05…6
Maximum peak current	A	2400 (10 ms)	120 (500 ms)
Supply (& monitored) voltage U_N	V AC	3 x 230/400…3 x 240/415	3 x 230/400…3 x 240/415
Operating range		$(0.8…1.2)U_N$	$(0.8…1.2)U_N$
Frequency	Hz	50/60	50/60
Power consumption per phase	W/VA	≤ 1/3.5	≤ 1/3.5
CT burden (per phase)	VA	—	0.04
Display		Eight digit counter - backlit LCD display	
Max. totalising count/Min. increment	kWh	999 999.99/0.01	999 999.99/0.01
LED pulses per kWh		1000	10 000
LED pulse length	ms	10±0.5	10±0.5
Ethernet technical data			
Bus system		Ethernet TCP	Ethernet TCP
Protocol		Modbus TCP, HTTP, NTP; DHCP	Modbus TCP, HTTP, NTP; DHCP
Conforms to standard		IEEE 802.3	IEEE 802.3
Communication speed	Mbps	10/100	10/100
Open collector- output specification (SO+/SO–)			
Number/Type		1 opto-isolated output	1 opto-isolated output
Voltage range/Maximum current (conform to EN 62053-31)	V DC/mA	3.3…27/1…27	3.3…27/1…27
Pulses per kWh**	Imp/kWh**	100	See table page 13
Pulse length	ms	50 ± 2	50 ± 2
Technical data			
Accuracy class		B	B
Ambient temperature (Within accuracy class)	°C	–25…+55	–25…+55
Protective class		II	II
Protection category: Housing/terminals		IP 50/IP 20	IP 50/IP 20
Approvals (according to type)		CE	

Ordering information

Example: Energy meter 32 A/230 V AC, with PTB certified, with MID certification, Class B accuracy, for 35mm rail (EN 60715) mounting. Available with Tamper-proof lead sealed cover as accessory.

7 E . 1 3 . 8 . 2 3 0 . 0 0 1 0

Series

Function
1 = 1-phase
3 = 3-phase

Current
2 = 25 A
3 = 32 A
6 = 65 A

Supply version
8 = AC 50 Hz

Supply voltage
230 = 230 V AC 50 Hz
400 = 3 x 230/400 V AC 50 Hz

Option
0 = SO +/- pulse output

Special version
0 = Standard
1 = MID compliant versions

Option
0 = Standard
2 = Standard (7E.12)
2 = Dual tariff (7E.36)

All versions/width
7E.12.8.230.0002/35 mm
7E.13.8.230.0010/17.5 mm
7E.16.8.230.0010/35 mm
7E.36.8.400.0010/70 mm
7E.36.8.400.0012/70 mm

E

Technical data

Insulation EN 62053-21			**7E.12, 7E.13, 7E.16**		**7E.36**	
Insulation rated voltage		V	250		250	
Overvoltage category			IV		IV	
Insulation	between active parts and SO+/SO– terminals	kV (1.2/50 µs)	6		6	
	between adjacent phases	kV (1.2/50 µs)	—		6	
Insulation	between supply and SO+/SO–	V AC	4000		4000	
	between adjacent phases	V AC	—		4000	
Protection class			II		II	
EMC Specification			**Reference standard**			
Electrostatic discharge	contact discharge		EN 61000-4-2		8 kV	
	air discharge		EN 61000-4-2		15 kV	
Radio-Frequency Electromagnetic Field (80…1000)MHz			EN 61000-4-3		10 V/m	
Fast Transients (Burst) (5-50 ns, 5 kHz)	on Supply terminals		EN 61000-4-4		Class 4 (4 kV)	
	on SO+/SO– terminals		EN 61000-4-4		Class 4 (2 kV)	
Surge (1.2/50 µs)	on Supply terminals		EN 61000-4-5		Class 4 (4 kV)	
	on SO+/SO– terminals		EN 61000-4-5		Class 3 (1 kV)	
Radio-Frequency Common Mode (0.15…80)MHz on Supply terminals			EN 61000-4-6		10 V	
Radiated and Conducted Emission			EN 55022		Class B	
Other data						
Pollution degree			2			
Vibration resistance	(10…60)Hz	mm	0.075			
	(60…150)Hz	g	1			
Vibration resistance of the internal mechanical counter (10…500)Hz		g	2			
Shock resistance		g/18 ms	30			
Shock resistance of the internal mechanical counter		g/18 ms	350			
Power lost to the environment			**7E.12, 7E.13**	**7E.16**	**7E.36**	
	without current	W	0.4	0.4	1.5	
	with maximum current	W	1	2	6	
Supply terminals			**7E.12, 7E.13**		**7E.16, 7E.36**	
	Max. wire size		solid cable	stranded cable	solid cable	stranded cable
		mm²	1…6	0.75…4	1.5…16	1.5…16
		AWG	18…10	18…12	16…6	16…6
	Screw torque for I_{max}	Nm	0.8…1.2		1.5…2	
	Screw		Pozidriv No.1, Flat No.1, 2			
SO+/SO– terminals	Max. wire size		solid cable	stranded cable	solid cable	stranded cable
		mm²	2.5	1.5	2.5	1.5
		AWG	14	16	14	16
	Screw torque for I_{max}	Nm	0.5		0.8	
	Screw		Pozidriv No.0, Flat No.1		Pozidriv No.0, Flat No.2	

V-2018, www.findernet.com

Ordering information - Energy meter

Example: 3-phase energy meter for current transformer operation (6A/400 V AC), with MID certification, Class B accuracy, for 35 mm rail (EN 60715) mounting. Supplied accessories: Tamper-proof lead sealed cover as accessory.

7	E	.	8	6	.	8	.	4	0	0	.	0	1	1	2

Series

Function
6 = 1-phase, backlit display
7 = 3-phase, backlit display, direct connection
8 = 3-phase, backlit display, for current transformer operation

Current
4 = 40 A
6 = 6 A (up to 50 000 A, using 7E.86 and CT)
8 = 80 A

Supply version
8 = AC 50/60 Hz

Supply voltage
230 = 230 V AC 50/60 Hz
400 = 3 x 230/415 V AC 50/60 Hz

Option
0 = SO pulse output
1 = Infra-red comms. port + two SO pulse outputs
2 = RS485 Modbus integrated interface + SO pulse output
3 = M-Bus integrated interface + SO pulse output
4 = Ethernet integrated interface plus SO pulse output

Special version
0 = Standard

Version
0 = Standard
1 = Conforms to MID directive

Special version
0 = Single tariff
1 = kWh only (0001)
2 = Dual tariff
3 = Panel mounting

Table 1

Imp/kWh*	CT ratio
1000	1…4
200	5…24
40	25…124
8	125…624
1	625…3124
0.1	3125…10 000

*Imp/kWh, Imp/kvarh, Imp/kVAh

Available versions

Infra-red comms. port for use with communication modules

Modbus	M-Bus	Ethernet	SO only
7E.78.8.400.0112	7E.64.8.230.0210	7E.64.8.230.0310	7E.78.8.400.0410	7E.64.8.230.0001
7E.86.8.400.0112	7E.78.8.400.0212	7E.78.8.400.0312	7E.86.8.400.0410	7E.64.8.230.0010
	7E.86.8.400.0212	7E.86.8.400.0312		

Technical data

Insulation			**7E.64.8.230.0xxx**	**7E.78.8.400.0xxx**	**7E.86.8.400.0xxx**
Insulation rated voltage		V	250	250	250
Insulation	between active parts and SO+/SO– terminals	kV (1.2/50 µs)	6		
	between supply and Modbus, M-Bus terminal	kV (1.2/50 µs)	6		
	between adjacent phases	kV(1.2/50 µs)	n/a		
Insulation	between active parts and SO+/SO– terminals	V AC	4000		
	between supply and Modbus, M-Bus terminal	V AC	4000		
	between adjacent phases	V AC	n/a		
Protection class			II		

EMC Specification according to 61000-4-(2/3/4)		**7E.64.8.230.0xxx**	**7E.78.8.400.0xxx**	**7E.86.8.400.0xxx**
Electrostatic discharge	contact discharge	8 kV		
	air discharge	15 kV		
Radio frequency Electromagnetic field (80…2000)MHz		30 V/m		
Fast Transients (burst) (5-50 ns, 5 kHz)	on Supply terminals	4 kV		
	on SO+/SO– terminals	2 kV		
	Modbus, M-Bus terminal	2 kV		
Surge (1.2/50 µs)	on Supply terminals	4 kV		
	on SO+/SO– terminals	1 kV		
	Modbus, M-Bus terminal	1 kV		

Other data		**7E.64.8.230.0xxx**	**7E.78.8.400.0xxx**	**7E.86.8.400.0xxx**
Pollution degree		2		
Vibration resistance		EN 60068-2-6	EN 60068-2-6	EN 60068-2-6
Shock resistance		EN 60068-2-27	EN 60068-2-27	EN 60068-2-27
Power lost to the environment	Max value per phase	0.5W/1.5 VA	1W/7.5VA	1W/7.5VA
	CT burden	—	—	0.04 VA/per phase

Supply terminals			**7E.64.8.230.0xxx**		**7E.78.8.400.0xxx**		**7E.86.8.400.0xxx**	
Max. wire size			solid cable	stranded cable	solid cable	stranded cable	solid cable	stranded cable
		mm^2	max 6	1.5…6	max 35	1.5…35	max 6	1.5…6
		AWG	—	—	—	—	—	—
Screw torque for I_{max}		Nm	1.5	1.5	2	2	1.5	1.5

SO+/SO– terminals, RS485 Modbus, M-Bus			**7E.64.8.230.0xxx**		**7E.78.8.400.0xxx**		**7E.86.8.400.0xxx**	
Max. wire size			solid cable	stranded cable	solid cable	stranded cable	solid cable	stranded cable
		mm^2	max 2.5	0.14…2.5	max 2.5	0.14…2.5	max 2.5	0.14…2.5
		AWG	—	—	—	—	—	—
Screw torque		Nm	0.5	0.5	0.5	0.5	0.5	0.5

Mechanical Display Type 7E.12, 7E.13, 7E.16, 7E.36

LED indication (Normal operation)

Type	Energy consumption			Pulses per kWh	Pulse space	The LED Pulse rate represents the instantaneous power being consumed, according to the following
	None	Low	High			
7E.12 7E.13				2000	100 ms	kW = (number of pulse per Minute) / 33.3
7E.16				1000	100 ms	kW = (number of pulse per Minute) / 16.7
7E.36				100	150 ms	kW = (number of pulse per Minute) / 1.7

LED indication (Abnormal operation)

Status indicates errors of installation, as below


Type 7E.12, 7E.13, 7E.16

Device ON, incorrect connection (L-N inverted).
Mark = 600 ms, Space = 600 ms




Type 7E.36


Mark = 100 ms,
Phase L1↑ L1↓ inverted or loss




Phase L2↑ L2↓ inverted or loss




Phase L3↑ L3↓ inverted or loss




Phase L1↑ L1↓ and L2↑ L2↓ inverted or loss




Phase L1↑ L1↓ and L3↑ L3↓ inverted or loss



Phase L2↑L2↓ and L3↑L3↓ inverted or loss




Phase L1↑L1↓ and L2↑L2↓ and L3↑L3↓ inverted or loss



SO+/SO– Open collector output wiring diagram Type 7E.12, 7E.13, 7E.16, 7E.36

The pulsating open collector output available at terminals SO+ and SO– can be interfaced with the input of a computer, plc or other energy management equipment to allow the remote monitoring of energy consumed.




Energy meters – at difference locations
(Note: Both Single and Dual tariff meters provide only a single pulsating output)

Central monitoring/management system
(max. 20 mA for each input)


SO-Output Type 7E.12, 7E.13, 7E.16

SO+/SO– Open collector output



SO-Output Type 7E.36


SO+/SO– Open collector output




V-2018, www.findernet.com

Outline drawings


Type 7E.12.8.230.0002/7E.16.8.230.0010




Type 7E.13.8.230.0010




Type 7E.36.8.400.0010




Type 7E.36.8.400.0012




Type 7E.64.8.230.0001




Type 7E.64.8.230.0010



Type 7E.78.8.400.0112




Type 7E.86.8.400.0112




V-2018, www.findernet.com

Outline drawing


Type 7E.64.8.230.0210




Type 7E.64.8.230.0310




Type 7E.78.8.400.0212




Type 7E.86.8.400.0212




Type 7E.78.8.400.0312




Type 7E.86.8.400.0312



Type 7E.78.8.400.0410



Type 7E.86.8.400.0410



V-2018, www.findernet.com

Accessories



07E.13

Terminal cover for type 7E.13	07E.13

For the tamper-proof lead seal use two terminal covers



07E.16

Terminal cover for type 7E.12, 7E.16 and 7E.36	07E.16

7E.12, 7E.16 - For the tamper-proof lead seal use two terminal covers
7E.36 - For the tamper-proof lead seal use four terminal covers

Terms and definitions

I	The electrical current flowing through the meter
I_n	The specified reference current for which the meter has been designed
I_{st}	The lowest declared value of "I" at which the meter registers active electrical energy at unity power factor (polyphase meters with balanced load)
I_{min}	The values of "I" above which the error lies within maximum permissible errors (MPEs) (polyphase meters with balanced load)
I_{tr}	The value of "I" above which the error lies within the smallest MPE corresponding to the class index of the meter
I_{max}	The maximum value of "I" for which the error lies within the MPEs

Detailed structure of the protocol is available on line

V-2018; www.findernet.com