TEGERA®



A high-visibility knitted glove with yellow nitrile dots and with touchscreen functionality.

TEGERA® 8821R

Learn more

VERY DURABLE AND HEAT PROTECTIVE

A high visibility knitted glove for precision work in dry-to moist environments. Flexible and soft with touchscreen functionality ensuring seamless transition between duties without having to remove the glove. Nitrile foam dipping with yellow Nitrile dots in the palm for ultimate grip. Made of 15 gg fibre to ensure all-day comfort. Retail packs are delivered with descriptive hangtags to help customers with their in-store choice.

CHARACTERISTICS

- Very durable
- Good fingertip sensitivity
- Flexible
- Good grip
- Comfortable

FUNCTIONS

- Withstands contact heat up to 100°C
- For touchscreen
- Latex-free
- High visibility colour

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Abrasion injuries, blisters, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Agricultural work, airport work, assembly, building and construction, construction, repair work, transport work, warehouse work

PRIMARY INDUSTRIES OF USE

Agriculture, rubber and plastic, machinery and equipment, mro, transportation, utilities, building and construction, logistics

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Heat protection gloves, Precision work gloves
CATEGORY Cat. II
LINING MATERIAL 15 gg, Polyester, Spandex
LENGTH 205-270 mm
DEXTERITY 5
GRIP DESIGN Dots
COLOUR Black, Yellow
PAIRS PER: BUNDLE/CARTON 6/72
DISPLAY TYPE Hangtag with euro slot
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam, Nitrile-dots
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
INNER MATERIAL SPECIFICATION Polyester, Elastane
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE

CE Cat. II
TP TC 019:2011

UKCA Cat. II
Information/UIS

EAC
EN 407:2020 (No flame protection) X1XXXX

EN 388:2016+A1:2018 4131X

EN ISO 21420:2020

ANSI 4 ABR

OEKO TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com

ORIGINAL 04 EXCELLENT 2019 dermatest® dermatest-guarantee.de

Contact heat rating valid for palm area only

FEATURES

For touchscreen

SIZE		ARTICLE NUMBER	EAN
6	XS	8821R-6	7340118392110
7	S	8821R-7	7340118392202
8	M	8821R-8	7340118392295
9	L	8821R-9	7340118392387
10	XL	8821R-10	7340118392479
11	XXL	8821R-11	7340118392561
12	3XL	8821R-12	7340118392653

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.