Date: 12/04/2023

PSD-4; 0...4 bar abs ; one switching output (PNP/NPN) + 4...20 mA

PSD-4; 0...4 bar abs ; one switching output (PNP/NPN) + 4...20 mA

Item number:	48780674
Quantity:	1 pcs.
Order code:	PSD-4-AZ-BA340-HDLZ-WZ-ZZ W1011PS4Z-SZAB-P-GSFI
Overview:	PSD-4; 0...4 bar abs ; one switching output (PNP/NPN) + 4...20 mA Electronic pressure switch with display Output signal: one switching output (PNP/NPN) + 4...20 mA IO-Link: without Power supply: 15...35 V DC Measuring range: 0...4 bar abs Process connection: G 1/4 A DIN EN ISO 1179-2 Sealing: FPM/FKM Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4 Accuracy: ± 0.5% of span Approvals: without with test protocol Specifications according to data sheet: PE 81.86
Details:	PSD-4; 0...4 bar abs ; one switching output (PNP/NPN) + 4...20 mA Electronic pressure switch with display Output signal: one switching output (PNP/NPN) + 4...20 mA IO-Link: without Power supply: 15...35 V DC Measuring range: 0...4 bar abs Process connection: G 1/4 A DIN EN ISO 1179-2 Sealing: FPM/FKM Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4 Accuracy: ± 0.5% of span Approvals: without with test protocol Specifications according to data sheet: PE 81.86

© 2023 - WIKA Instruments s.a.r.l.