rotronic

Datenblatt - Fiche technique - Data sheet


11.04.5511




ROLINE GOLD Monitorkabel DVI, ST-ST, (24+1) dual link, 1,0m

ROLINE Câble pour écran DVI GOLD, M-M, (24+1) dual link, 1,0m

ROLINE Gold Monitor Cable, DVI M – DVI M, (24+1) dual link, 1 m



PIN Assignment



ELECTRICAL TEST:

1.100% OPEN SHORT & MIS WIRE TEST
2.CONTACT RESISTANCE:2 OHM(MAX)
3.INSULATION RESISTANCE:10M OHM(MIN)
4.HI-POT TEST:DC 300V/10ms

NO	DESCRIPTION	QTY	UNIT
13	Wire Clip OD:7.3mm	2	pcs
12	Ferrite core28.5*17.5*11.5MM	2	pcs
11	DVI M TRANSPARENT DUST COVER	2	pcs
10	DVI 24# Yellow down Shell aluminium alloy laser etching DVI LOGO	2	pcs
9	DVI 24# Yellow up Shell aluminium alloy laser etching DVI LOGO	2	pcs
8	#4-40UNC 4*38.5 Gold-plated screws	4	pcs
7	TUBE BLACK : ∮1.5*22mm THICK	0.044	m
6	TUBE BLACK : ∮1.0*12mm THIN	0.168	m
5	BLACK Ø2.0*10mmTHIN	0.14	m
4	45P BLACK PVC	40	g
3	TRANSPARENT PE	6	g
2	DVI(24+1) M SOLDER TYPE, GOLD PLATED SHELL, BLACK INSULATION	2	pcs
1	UL20276 (30AWG*1PR+EAM)*7C+30AWG*1PR+30AWG*3C+AEB 85%AL OD:7.3MM WITH BLACK/YELLOW NET	1	M

	TOLERANCE INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

DRAWN BY
CHECK BY
APPD BY

rotronic

11.04.5511

ROLINE GOLD DVI Cable, Dual Link , M / M
1m, black w/yellow & black nylon net

SCALE	NONE	DRAWING NO:	REV A
UNIT	MM		
DATE	2013.07.26		1/1