# Product datasheet
## Characteristics

# xs212sanal2
inductive sensor XS2 M12 - L55mm - stainless - Sn7mm - 12..24VDC - cable 2m



## Main

| | |
|---|---|
| Range of product | OsiSense XS |
| Series name | Application |
| Sensor type | Inductive proximity sensor |
| Product specific application | Food and beverage |
| Sensor name | XS2 |
| Sensor design | Cylindrical M12 |
| Size | 55 mm |
| Body type | Fixed |
| Detector flush mounting acceptance | Non flush mountable |
| Material | Stainless steel |
| Type of output signal | Discrete |
| Wiring technique | 3-wire |
| [Sn] nominal sensing distance | 7 mm |
| Discrete output function | 1 NO |
| Output circuit type | DC |
| Discrete output type | NPN |
| Electrical connection | Cable |
| Cable length | 2 m |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Switching capacity in mA | <= 200 mA with overload and short-circuit protection |
| IP degree of protection | IP68 double insulation conforming to IEC 60529<br>IP69 K conforming to DIN 40050 |

## Complementary

| | |
|---|---|
| ISO thread | M12 x 1 |
| Detection face | Frontal |
| Front material | PPS |
| Enclosure material | Stainless steel 316 L |
| Operating zone | 0...5.6 mm |
| Differential travel | 1...15% of Sr |
| Cable composition | 3 x 0.34 mm² |
| Wire insulation material | PVC |
| Status LED | 1 LED yellow for output state |
| Supply voltage limits | 10...36 V DC |
| Switching frequency | <= 2500 Hz |
| Voltage drop | <= 2 V at closed state |
| Current consumption | <= 10 mA at no-load |
| Delay first up | <= 10 ms |
| Delay response | <= 0.2 ms |
| Delay recovery | <= 0.2 ms |
| Marking | CE |
| Threaded length | 38 mm |
| Length | 55 mm |
| Product weight | 0.075 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| Product certifications | CSA<br>UL |
| Ambient air temperature for operation | -25...85 °C |
| Ambient air temperature for storage | -40...85 °C |
| Vibration resistance | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS | Compliant - since 0936 - Schneider Electric declaration of conformity |
| Product environmental profile | Available |
| Product end of life instructions | Available |