Vitoject® 890



Application

- chemical industry
- laboratories
- manufacturing of chemicals
- printing industry
- metal and plastics processing
- recycling and waste disposal
- fire brigades
- cleaning and maintenance
- etching

Qualities and advantages

- very good protection against extremely aggressive and toxic chemicals
- very high gas tightness
- solvent-free by eco-friendly injection moulding process
- excellent wearing comfort
- very good temperature flexibility
- material is highly resistant to ozone and sunlight (UV)

Article no. **Name**	**890** Vitoject® 890
Material	fluorocarbon rubber
Description	rolled edge, smooth, powdered
Length (mm) **Total thickness (mm)**	340 -360 0,7 ± 0,1
Colour **Size**	black 8, 9, 10, 11
Classification	category III EN388:2016 3101X · ISO 374-1/Type A DFGKLM · ISO 374-5 Virus







Features

- AQL ‹ 0,65
- manufactured by Vulkoject process technology
- wide shape makes it possible to wear gloves underneath (heat protection)
- after contamination with specific chemicals a reconditioning, special cleaning process, is possible (in agreement with the KCL-laboratory)
- can be combined with chemical protective clothing
- excellent low degradation
- good resistance against polycyclic aromatic hydrocarbons (petrochemistry)

www.kcl.de
sales@kcl.de

by Honeywell

KCL GmbH
Industriepark Rhoen
Am Kreuzacker 9
36124 Eichenzell
Germany
Phone +49 6659 87-300
Fax +49 6659 87-318

V300818 GB

Honeywell