

BLK 5.0 E

Nibbler up to 5 mm

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 47 61 00 0

Details

- Suited to cuts over 90° edges, for example on guard rails or during tank decommissioning.
- Incredible power delivered by the 1700 W motor while also offering outstanding ergonomics and optimum power-to-weight ratio.
- Extensive user protection: restart protection, blocking protection, overload protection, soft start.
- Cutting direction: 4 x 90°, can be adjusted without the need for tools.
- Variable stroke.
- Tool-free quick change system for die and punch.
- Ergonomic handle suited to guiding in all directions.
- Chip protection mesh in fan area.
- Wide range of accessories.

Price includes

- 1 die 5, steel (31309107000) fitted
- 1 punch 5/P5 steel (31309141000) fitted
- 1 additional handle fitted
- 1 plastic tool case (L-BOXX 238)

Product feature

- Cutting direction
- QuickIN
- Adjustable stroke
- Additional handle

Application

Curve cuts	+
Interior cut-outs	+
Profile sections	++
Notches	++

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	1,700 W
Output	1,000 W
Strokes	820 rpm
Cutting speed	1,5 m/min
Steel up to 400 N/mm²	5 mm
Steel up to 600 N/mm²	3.3 mm
Steel up to 800 N/mm²	2.5 mm
Non-ferrous metals up to 250 N/mm²	7 mm
Cutting width	8 mm
Immersion Ø with die	43 mm
Rad. of smallest curve (inside/outside)	90 / mm
Cable with plug	4 m
Weight according to EPTA	3.80 kg
Weight according to EPTA	3.80 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	95,8 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	103,8 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	112,4 dB 3 dB
Vibration value 1 αhv 3-way Uncertainty of measured value Kα	12,4 m/s² 1,5 m/s²

Application examples





