



jalas® FLOW 9615

EN ISO 20345:2011 S3, SRC, HRO

Learn more

LOW SHOE WITH HEAT RESISTANT OUTSOLE

Low shoe with heat resistant outsole. Durable microfiber and durable textile make this safety shoe long-lasting. Nail protection in plasma-treated composite (PTC) textile, PU midsole, rubber outsole and toecap in aluminium. Suitable for both outdoor and indoor environments.

CHARACTERISTICS

- Extra comfortable
- Excellent shock absorption
- Perfect fit
- Light

FUNCTIONS

- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Stabilizator
- Water repellent
- Conforms with IEC 61340-5-1 (ESD)
- Double shock absorption zones
- Extra shoelaces
- Anatomically designed

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Narrow/Regular
COLLECTION Flow
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester
INSOLE FX3 Supreme
INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING Laces
COLOUR Black, Turquoise
NET WEIGHT, (SIZE 42) 1.06 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN ISO 20345:2011 S3, SRC, HRO

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Heat-resistant outsole
- Water repellent
- Nail protection in plasma-treated composite (PTC) textile
- Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9615-34	6408487505584
35	2	3½	4	9615-35	6408487505591
36	3	4	5	9615-36	6408487505607
37	4	5	6	9615-37	6408487505614
38	5	5½	6½	9615-38	6408487505621
39	6	6½	7½	9615-39	6408487505638
40	6½	7½	8½	9615-40	6408487505645
41	7	8	9	9615-41	6408487505652
42	8	9	10	9615-42	6408487505669
43	9	9½	11	9615-43	6408487505676

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.