NEW

n-fuze

S3 EN ISO 20349-2:2017+A1:2020 - S3 - SRC
HRO - CI - HI - WG



■ **4834 black** | 36▶51

PRODUCT CHARACTERISTICS

- HRO +300°C (high heat-resistance)
- Non-magnetic
- Leather upper
- Offset heel

EXTRAS PARADE TECHNOLOGY

- VPS SYSTEM — Supports the arch of the foot
- FLEX SYSTEM — Helps expel soil



FASTENS AT THE SIDE WITH VELCRO



PARA-ARAMID YELLOW STITCHING RESISTANT TO MOLTEN METAL SPRAY AND SPARKS

COMPOSITION

Upper	Coated split leather
Linning	3D Mesh
Toe Cap	Composite
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Non-metallic
Sole	PU inter / Nitrile rubber half-sole
Weight for size 42*	780g * Weight per shoe

**

Size coefficient 42	Flat		Heel	
	Standard	Parade	Standard	Parade
Ceramic/Nals flooring (soap solution)	0,32	**0,49**	0,28	**0,51**
SR Ceramic + glycerine flooring	0,18	**0,19**	0,13	**0,18**

SAFETY TABLE

- Toe cap (200J)
- P — Antipuncture sole
- SRC — Antislip sole **
- E — Shock-absorption
- A — Antistatic
- FO — Oil and fuel resistant shoe
- WRU — Water-repellent upper

PARADE SAS • Route de Chaudron - St-Pierre-Montlimart - 49110 Montrevault-sur-Èvre - France • Ph. +33(0) 2 41 75 32 37 • Mail: contact@parade-protection.com
Parade reserves the right to modify the product's manufacturing. ©Parade, All rights reserved. Non-contractual document. Update December 2022