Date: 11/04/2023

TG54.100/1, DS, 0...200°C , L1=150 mmx6mm

Model: TG54.100

Item number:	48806892
Quantity:	1 pcs.
Order code:	TG54.100DS-1-C1LZ-BK-B0150GZ-ZAHAZZZ TO F-1IO-AZ1ZZZZZ2ZZZZ
Overview:	TG54.100/1, DS, 0...200°C , L1=150 mmx6mm Process connection: plain, without thread flat instrument glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Ingress protection: IP 65 Permissible ambient temperature: -40 ... +100 °C *WIKA* with Serial number
Details:	Model: TG54.100 Specifications according to data sheet: TM 54.02 Accuracy class: class 1 per EN 13190 Nominal size: 100 Connection location: back mount, adjustable Connection design: 1, plain stem Process connection: plain, without thread Scale range: 0 °C ... 200 °C Stem diameter: 6 mm Insertion length L1: 150 mm Window: flat instrument glass Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Ingress protection: IP 65 Permissible ambient temperature: -40 ... +100 °C with Serial number Manufacturer logo: *WIKA*

© 2023 - WIKA Instruments s.a.r.l.