
Inductive sensor

BES 516-356-E5-C-S4
BES00UY

BALLUFF
sensors worldwide




- **PNP**
- **Normally open (NO)**
- **4.00 mm**
- **Non embeddable**
- **Connector, M12x1-S04**


General attributes

Approvals / Conformity	CE cULus EAC
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP68 according to BWN PR 20
Function indicator	Yes
Polarity reversal protected	Yes
Power indicator	No
Protection Class	II
Short circuit protected	Yes
MTTF	830 a

Electrical attributes

Connection type	Connector
Eff. operating current Ie	200 mA
Eff. operating voltage Ue DC	24.0 V
Electrical version	DC, direct current
Load capacitance max. (at Ue)	0.500 µF
Max. no-load cur. Io undamped	4.0 mA
Minimum operating current Im	0 mA
No-load current Io damped max.	10.0 mA
Operating voltage UB max. DC [V]	30.0 V
Operating voltage UB min. DC [V]	10.0 V
Rated insulation voltage Ui	250 VAC
Rated short circuit current	100 A
Ripple max. (% of Ue)	15 %
Switching freq. f max. (at Ue)	2000 Hz





LISTED IND. CONT. EQ. 81U2 for use in the secondary of a class 2 source of supply

IND. CONT. EQ 81U2 for use in the secondary of a class 2 source of supply Environmental - Type 1 Enclosure

Switching function	Normally open (NO)
Switching output	PNP
Voltage drop static max.	2.0 V

Mechanical attributes

Ambient temperature Ta max.	70 °C
Ambient temperature Ta min.	-25 °C
Assured operating distance Sa	3.20 mm
Connector type	M12x1-S04
Depth	49.5 mm
Diameter d1	M12x1
Eff. operating distance Sr	4.00 mm
Housing material	CuZn
Mech. installation condition	Non embeddable
Mounting length	29.5 mm
Rated operating distance Sn [mm]	4.00 mm
Sensing face material	PBT
Surface protection	Nickel-plated
Tightening torque	15 Nm

Remarks

The sensor is functional again after the overload has been eliminated.

For further information on MTTF/B10d, please refer to the MTTF / B10d Certificate.

Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.