PRODUCT-DETAILS

OT30F4N2

OT30F4N2 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT30F4N2
Product ID	1SCA108347R1001
EAN	6417019416472
Catalog Description	OT30F4N2 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible diconnect switch with front protected clamp terminals, handle and shaft are not included

ABB EcoSolutions

Environmental Information	1SCC301183D0201
Environmental Product Declaration - EPD	1SCC301280D0201

Material Compliance

Conflict Minerals	9AKK108467A5658

© 2024 ABB. All rights reserved.

Reporting Template (CMRT)	
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301060M0004
Mechanical Drawings	1SCC301468F0001 1SCC301467F0001 OT100-125F4N2.stp OT100-125F4N2.igs
Environmental Product Declaration - EPD	1SCC301280D0201

Environmental

Degree of Protection	Front IP20
Environmental Information	1SCC301183D0201
Pollution Degree	3

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	96.5 mm
Product Net Height	100 mm
Product Net Depth / Length	86 mm
Product Net Weight	0.43 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	109 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	86 mm
Package Level 1 Gross Weight	0.46 kg
Package Level 1 EAN	6417019416472

© 2024 ABB. All rights reserved.

Technical

Cable Cross-Section	Cu 2.5 ... 25 mm²
Connecting Capacity Main Circuit	Flexible 1x Cu 2.5…25 mm² Stranded 1x Cu 2.5…25 mm²
Degree of Protection	Front IP20
Distance Between Phases	Standard
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Handle Color	Black
Handle Type	Knob Handle and shaft not included
Lock Type	No
Mechanical Durability	20000
Mounting Type	Base mounting
Number of Poles	4P
Operating Mode	Front operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 0.7 W
Rated Conditional Short-Circuit Current (I_{nc})	(125 A fuse, 415 V) 50 kA (125 A fuse, 690 V) 10 kA (63 A fuse, 690 V) 50 kA
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 18.5 kW (500 V) 22 kW (690 V) 37 kW
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 3.6 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 2.5 kA
Recommended Screw Driver	Main Circuit Hexagon 4
Special Functions	No
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Switches Operating Mechanism	Mechanism on Top of the Switch
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 6.2 N·m
Wire Stripping Length	Main Circuit 17-18 mm

© 2024 ABB. All rights reserved.

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	30 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 30 Hp
Wire Size	1x 12-2/0 AWG 2x 12-4 AWG
Wire Stripping Length	Main Circuit 17-18 mm
Recommended Screw Driver	Main Circuit Hexagon 4
Tightening Torque	acc. IEC 60947-1 6.2 N·m
Tightening Torque UL/CSA	55 in·lb

Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301010D0201
UL Certificate	cULus certificate OT30-125
VDE Certificate	No certification needed

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601468

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

© 2024 ABB. All rights reserved.



© 2024 ABB. All rights reserved.