Specifications

# Eaton 088059



## Catalog Number: 088059

Eaton Moeller® series RMQ16 Indicator light, flush, white, +filament lamp, 24 V Q18LF-WS/WB

### General specifications

**Product Name**
Eaton Moeller® series RMQ16 Indicator light

**Catalog Number**
088059

**EAN**
4015080880592

**Product Length/Depth**
59 mm

**Product Height**
18 mm

**Product Width**
18 mm

**Product Weight**
0.009 kg

**Certifications**
CE
IEC/EN 60947
UL
IEC/EN 60947-5
UL Category Control No.: NKCR
CSA File No.: 46552
UL 508
CSA
CSA Class No.: 3211-03
CSA-C22.2 No. 14-05
UL File No.: E29184

Powering Business Worldwide

## Product specifications

### Type

Indicator lights

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

eaton-rmq-titan-brochure-br047004en-en-us.pdf

### Declarations of conformity

DA-DC-00004136.pdf

DA-DC-00004158.pdf

### Drawings

eaton-operating-pushbutton-rmq16-dimensions-002.eps

eaton-operating-indication-rmq16-indicator-light-3d-drawing-002.eps

116C076

### eCAD model

DA-CE-ETN.Q18LF-WS_WB

### Installation instructions

IL04716016Z

### mCAD model

DA-CD-leucht_18

DA-CS-leucht_18

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### Fitted with:

Front ring

### Pollution degree

3

### Climatic proofing

Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

### Connection to SmartWire-DT

No

### Rated impulse withstand voltage (Uimp)

800 V AC

### Bezel color

Black

### Shock resistance

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27

### Bezel material

Plastic

### Terminal capacity

0.5 - 1.0 mm²

Lens color

White

Design

Flat

Mounting position

As required

Terminal size

2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors

Overvoltage category

III

Degree of protection

NEMA 1

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

25 °C

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Opening diameter

16 mm

Opening height

16 mm

Rated insulation voltage (Ui)

250 V

Rated operational current for specified heat dissipation (In)

0 A

Rated operational voltage (Ue) at AC - max

24 V

### Static heat dissipation, non-current-dependent Pvs

1 W

### Suitable for number of built-in signal lights

1

### Width opening

0 mm

### Product category

RMQ16

### Size

Front dimensions: 18 x 18 mm

### Degree of protection (front side)

IP65

### Lens type

Flat

Square

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia