Date: 11/04/2023

F73.100/2, 0...120°C, L1=200 mmx12mm,

Gas actuated thermometer, stainless steel series

Item number:	48771787
Quantity:	1 pcs.
Order code:	F73.100-C1F-2GD-G0200-SE3-1-Z-HZZ-ZZZZZZ G7 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/2, 0...120°C, L1=200 mmx12mm, G 1/2 B radial bottom Surface mounting flange, stainless steel stainless steel armoured capillary Capillary length: 3.5 m laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: 0 °C ... 120 °C Connection design: 2, male nut Process connection: G 1/2 B Stem diameter: 12 mm Insertion length L1: 200 mm Capillary: stainless steel armoured capillary Capillary length: 3.5 m Design of case mounting: Surface mounting flange, stainless steel Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.