Specifications

# Eaton 095877

## Catalog Number: 095877

Eaton xEnergy Safety Ci LV systems LV switchgear. Panel enclosure, with gland plate and cable glands, HxWxD=375x375x275mm



## General specifications

**Product Name**
Eaton xEnergy Safety Ci empty enclosure insulated

**Catalog Number**
095877

**EAN**
4015080958772

**Product Length/Depth**
275 mm

**Product Height**
375 mm

**Product Width**
275 mm

**Product Weight**
3.884 kg

**Compliances**
IEC/EN 60439-1, VDE 0660 Part 500
RoHS conform

**Certifications**
EN 61439-2
EN 62208

Powering Business Worldwide

## Product specifications

### Used with

The reference values indicated in the table apply to the basic elements of the distribution board. As far as devices, terminals etc. fitted into the enclosures are concerned, their own specific technical data and rated values apply.

### Special features

Low-voltage fuses (IEC/EN 60269, VDE 0636) Sealable cover fasteners Sides closed, but with full area knockout Open top Fitting of cable supports in the distribution board with wedge-lock fastener Gland plate can be split, cables can be inserted from the front

### Type

Basic enclosure Panel enclosure with gland plates fitted xEnergy Safety Ci

### Features

Cover with overpressure release

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

### 10.13 Mechanical function

Meets the product standard's requirements.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Lower part: 960 °C / cover: 850 °C

### 10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

## Resources

### Brochures

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

### Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

### Drawings

eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-017.eps

eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-015.eps

eaton-enclosures-xenergy-safety-ci-lv-systems-dimensions-008.eps

eaton-insulated-boards-panel-xenergy-safety-ci-lv-systems-dimensions-004.eps

eaton-enclosures-mounting-xenergy-safety-ci-lv-systems-dimensions-007.eps

### Installation instructions

05670392.pdf

### 10.2.5 Lifting

20 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.

### 10.2.6 Mechanical impact

IK10

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

IP65

### 10.4 Clearances and creepage distances

Is the panel builder's responsibility.

### 10.5 Protection against electric shock

Protection class 2, therefore not applicable.

### 10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Ui = 1000 V AC

### 10.9.3 Impulse withstand voltage

8 kV

### 10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

### Surface finishing

Passivated

Galvanized

### Degree of protection

Other

IP00 (cable entry open)

IP64 (KST cable entries from above)

IP65 (KST cable entries from below)

IK10

IP65 (enclosure)

IP65

### Enclosure material

Plastic

Surface protection

Other

Circuit integrity

Other

Unit type

Stand-alone device

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-5 °C

Built-in depth

250 mm

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)

34 W

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)

29 W

Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890)

32 W

Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)

69 W

Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890)

59 W

Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890)

64 W

Color

Gray

Transparent, smoky gray (cover)

Light gray (RAL 7035, base)

Cover/door color

Transparent

Cover/door model

Closed

Cover/door type

None

Cover

Number of openings (flange plates)

4

Operating altitude without derating - max

2000 mm

Plate thickness (cabinet)

6 mm

Plate thickness (cover/door)

6 mm

RAL-number

7035

Width in number of modular spacings

15

Cable entry type

14 - 68 mm (3x)

Mounting method

Surface mounted (plaster)

Creepage and clearance distances

III/3 to IEC/EN 60439-1 (standard)

Number of rows

0

Functions

Extension possible

Flammability characteristics of glow rod test

VDE 0304 Part 3 level IIb, level IIb to IEC 60707

Protection class

II

Number of modules

1

Relative humidity

50 % (at 40 °C)

90 % (at 20 °C)

Internal depth

250 mm

Mean ambient operating temperature (24 hours)

35 °C

Mounting depth with mounting plate

250 mm

Nominal current

1600 A

Number of conduit inlets

100

Suitable for

Lightning protection

Outdoor use

Mounting grid

25 mm (DIN 43660)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia