

Generic photo of the product

Main technical characteristics of this part number

Family	*XCS-A*
Type of movement	*Translation*
Unlock actuator	*Without*
Product supply	*-*
Type of actuator	*Right key*
Position of the operator	*-*
Type of contact	*1 N/O+2 N/C break before make*
Type of signaling	*1 LED orange*
Cable entries	*1 entry 1/2" NPT*
Connection	*Terminal screw-clamp*
Material - case	*Metal*
Body dimensions (mm)	*40 x 113.5 x 44*
Mounting method	*2 slots Ø7.3 x 5.3*
Type of body	*Confined*
Mechanical life	*> 1 million operations*
Switching angle	*-*
Contact	*With dependant action*
Positive operation contact	*Yes*
Auxiliary contact	*Without*
Indicator lamp supply	*AC or DC 24/48 V*
Temperature of operation	*-25... + 70°C*
Degree of protection	*IP67*
Mechanical conformity	*IEC 68-2-6. IEC 68-2-27*
Certifications	*UL-CSA*
Product standards	*IEC/EN60947-5-1 IEC60947-5-3*
Machine standards	*IEC/EN60204-1/EN1088/EN292*

Generic description of the product

Preventa XCS key switch
Metal or plastic safety switches with tab wrench for mounting on door or housing of a machine with or without inertia.