DATASHEET - NZMH2-4-AF80-BT-NA

Circuit-breaker, 4p, 80A, box terminals

Part no. **NZMH2-4-AF80-BT-NA**
153394

General specifications

Product name	Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no.	NZMH2-4-AF80-BT-NA
EAN	4015081501649
Product Length/Depth	149 millimetre
Product height	206 millimetre
Product width	140 millimetre
Product weight	3.755 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 60947 UL 489 UL listed CE marking Specially designed for North America UL (File No. E31593) CSA-C22.2 No. 5-09 UL (Category Control Number DIVQ) IEC IEC 60947-2 UL/CSA
Product Tradename	NZM
Product Type	Molded case circuit breaker
Product Sub Type	Thermo-magnetic

Delivery program

Application	Use in unearthed supply systems at 690 V Branch circuits, feeder circuits
Type	Circuit breaker
Circuit breaker frame type	NZM2
Number of poles	Four-pole
Amperage Rating	80 A
Release system	Thermomagnetic release
Features	Motor drive optional Protection unit
Special features	Fixed overload releases Ir Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Rated current = rated uninterrupted current: 80 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Technical Data - Electrical

Voltage rating	690 V - 690 V
Rated operating voltage Ue (UL) - max	480 V
Rated insulation voltage (Ui)	1000 V AC
Rated impulse withstand voltage (Uimp) at auxiliary contacts	6000 V
Rated impulse withstand voltage (Uimp) at main contacts	8000 V
Current rating of neutral conductor	200% of phase conductor
Rated operational current	80 A (690 V AC-1, making and breaking capacity)
Rated short-time withstand current (t = 0.3 s)	1.9 kA
Rated short-time withstand current (t = 1 s)	1.9 kA
Instantaneous current setting (Ii) - min	6 A
Instantaneous current setting (Ii) - max	10 A
Overload current setting (Ir)	80 A - 80 A
Overload current setting (Ir) - min	80 A
Overload current setting (Ir) - max	80 A
Short delay current setting (Isd) - min	0 A

Short delay current setting (Isd) - max	0 A
Short-circuit release non-delayed setting - min	480 A
Short-circuit release non-delayed setting - max	800 A
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz	150 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz	150 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz	130 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz	37.5 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz	5 kA
Rated short-circuit making capacity Icm at 240 V, 50/60 Hz	330 kA
Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz	330 kA
Rated short-circuit making capacity Icm at 440 V, 50/60 Hz	286 kA
Rated short-circuit making capacity Icm at 525 V, 50/60 Hz	105 kA
Rated short-circuit making capacity Icm at 690 V, 50/60 Hz	40 kA
Short-circuit total breaktime	< 10 ms
Low-voltage HBC fuse - max	355 A gG/gL
Electrical connection type of main circuit	Frame clamp
Isolation	300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max	120
Handle type	Rocker lever
Utilization category	A (IEC/EN 60947-2)
Overvoltage category	III
Pollution degree	3
Lifespan, electrical	7500 operations at 690 V AC-1 5000 operations at 690 V AC-3 10000 operations at 400 V AC-1 6500 operations at 400 V AC-3
Direction of incoming supply	As required
Technical Data - Mechanical	
Mounting Method	Built-in device fixed built-in technique DIN rail (top hat rail) mounting optional Fixed
Degree of protection	IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side	IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)	IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
Protection against direct contact	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance	20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)	0
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0
Position of connection for main current circuit	Front side
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features	Fixed overload releases Ir Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Rated current = rated uninterrupted current: 80 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Lifespan, mechanical	20000 operations
Technical Data - Mechanical - Terminals	
Standard terminals	Box terminal
Terminal capacity (aluminum solid conductor/cable)	16 mm^2 (1x) at tunnel terminal
Design verification as per IEC/EN 61439 - technical data	
Rated operational current for specified heat dissipation (In)	80 A
Equipment heat dissipation, current-dependent	20.54 W
Ambient operating temperature - min	-25 °C

Ambient operating temperature - max	70 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	70 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Functions	Current limiting circuit breaker System and cable protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])

Rated permanent current Iu	A	80
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA	150
Overload release current setting	A	80 - 80
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	6 - 10
Power loss	W	20.5
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Frame clamp
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		Yes
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		4
Position of connection for main current circuit		Front side
Type of control element		Rocker lever

Complete device with protection unit			Yes
Motor drive integrated			No
Motor drive optional			Yes
Degree of protection (IP)			IP20

© 04/2023 by Eaton Industries GmbH