# 207 LED Installation Permanent Beacon





- Optimised illumination
- 360° visibility
- Suitable for use in the 22 mm standard control panel/switchgear programme
- Simple connection by means of 6.3 mm spades

Life duration up to 100,000 hrs

## TECHNICAL SPECIFICATIONS:

| | |
|---|---|
| Dimensions (Ø x Height): | 58 mm x 69 mm (Protrusion from panel) |
| Housing: | PA-GF, high impact |
| Lens: | PC, transparent, Ring: PC |
| Connection: | Spades 6.3 x 0.8 mm<br>Finger-proof model according to BGV A2, when used with insulated spades |
| Fixing: | Installation mounting for Ø 22.5 mm (M 22 x 1.5 mm) with anti-twist device |

## ORDER SPECIFICATIONS:

| Voltage | 24 V≂ | 115 V~ | 230 V~ |
|---|---|---|---|
| Current consumption | 45 mA | 25 mA | 25 mA |
| red | **207 100 75** | **207 100 67** | **207 100 68** |
| green | **207 200 75** | **207 200 67** | **207 200 68** |
| yellow | **207 300 75** | **207 300 67** | **207 300 68** |

Further colours and voltages on request.

## TECHNICAL DIAGRAMS:

see page 269

Sizes of Permanent Beacons



24 V PLC



WERMA SIGNALTECHNIK