PRODUCT-DETAILS

E6.2H 6300 Ekip Touch LSIG 4p F HR

E6.2H 6300 Ekip Touch LSIG 4p F HR



General Information

Extended Product Type	E6.2H 6300 Ekip Touch LSIG 4p F HR
Product ID	1SDA071926R1
EAN	8015644757762
Catalog Description	E6.2H 6300 Ekip Touch LSIG 4p F HR
Long Description	C.BREAKER SACE EMAX2 E6.2H 6300 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 6300 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1905 9AKK108468A1913

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	5997bd6c-7d4f-4420-abd3-5fb9bfeac9ad Italy (IT)
Simplified SCIP	fb8d84ab-ffec-4a62-8f7e-39f7621d130e Germany (DE) 09a812cf-6d87-4791-bddb-a1215a8432b2 Belgium (BE) 5bfe6044-7ce2-437c-acd8-47c637d666ba Germany (DE) d47fb5c9-c63e-4670-8927-d0a671a2a7a7 France (FR) f1bdbb6c-5195-4320-8d9d-1a8a21b336bd Croatia (HR) 74ae4c8b-87f1-4ab9-a121-3f02e1a0c4dd Norway (NO) c2fbec5b-196c-4343-b72f-a854df03e127 Poland (PL) 3914c7c9-ec82-4022-b5e0-04d79b132267 Sweden (SE) bea7d2ba-7fd2-4fe0-8220-6fe45fc822c3 Poland (PL) c81eb84d-249d-42c4-a23a-93965bc8a2cd Finland (FI) 5c1e8a46-e08f-42e8-b4dd-b240d5b23473 Sweden (SE) d354182f-8dba-4e56-b0af-b71fec62dbdf Belgium (BE) 2f8f0c1c-4d86-49c8-9530-88d32a4de94a Czech Republic (CZ) 4c943002-6a95-45e3-a954-06f357860749 Germany (DE) eb236fcf-7236-4b51-944b-9e291f1a23ef Poland (PL) d509d6c6-f8b1-4b4c-9f04-c97b06226db4 France (FR) 270f6c78-df21-4dcb-9d99-062e60a54ee5 Netherlands (NL) 03a50561-0d5e-4270-ba09-420b8b70c7ad Germany (DE) ac143af9-e033-4d75-9509-1f492724c84e Germany (DE) f5b3ba4e-58a3-45c3-8e54-ca578df9b793 Hungary (HU) cbe784e4-3902-4110-8982-775d850474fb Spain (ES) bf25a44b-0720-491c-b916-031abfce1e81 Hungary (HU) 9b095972-7ce5-4dd6-8072-6bce848818ec Estonia (EE) d92336eb-1487-440e-b24d-8db094a2a9e2 Greece (GR) 57b27cf0-0227-4609-af5f-3e7cd34edc1c Bulgaria (BG) bbf6f039-639b-4230-a318-76ebd17a5cff Portugal (PT) 15aa5991-b429-415f-8c9c-ec44df3d52ee Denmark (DK)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	ZDHYETBF000A000000XX
EAN	8015644757762
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	888 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	125 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	134 kg
Package Level 1 EAN	8015644757762

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0249

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 2000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	50 %
Number of Poles	4P
Power Loss	767 W
Rated Current (I_n)	6300 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	6300 A

© 2024 ABB. All rights reserved.

Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M12
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E6.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001060R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.