PRODUCT-DETAILS

E215-16-11G

Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 1NC, El. Color: Blue, MW: 0.5



General Information

Extended Product Type	E215-16-11G
Product ID	2CCA703155R0001
EAN	7612270938865
Catalog Description	Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 1NC, El. Color: Blue, MW: 0.5
Long Description	Pushbutton 1 NO + 1 NC, Rated current: 16A/250 VACPDC, Button colour: blue, Module width 0,5

Technical

Standards	EN60068-2-1 EN60068-2-2 EN60068-2-30 DIN EN 60669-1 VDE 0632-1 UL508
Rated Voltage (U_r)	Lamp 48 ... 48 V
Rated Operational Voltage	acc. to EN 250 V AC acc. to UL 508 240 V AC
Maximum Switching Voltage	250 V

© 2024 ABB. All rights reserved.

Rated Current (I_n)	16 A
Rated Frequency (f)	50/60 Hz
Power Loss	0.5 W
Power Watt	0.72 W
Number of Contacts NC	1
Number of Contacts NO	1
Number of Main Contacts NC	1
Number of Main Contacts NO	1
Number of Auxiliary Contacts CO (SPDT)	0
Number of Poles	2
Tightening Torque	1.2-1.5 N·m
Switch Type	Double Interrupting Contacts
Material of Conductor	Copper
Remarks	Sealable in the On and Off positions
Color	Blue
Control Element Color	Blue
Connecting Capacity	Solid 1x1…6 mm² Solid 2x2.5 mm² Flexible 1x0.75…2x2.5 mm²

Material Compliance

RoHS Information	2CCC441014D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	2CCC005047D0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20190425
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25…+55 °C Storage -40…+70 °C
Degree of Protection	IP20
Environmental Information	2CCC441003C0201

Dimensions

Width in Number of Modular Spacings	0.5
Product Net Width	9 mm
Product Net Height	85 mm
Product Net Depth / Length	68 mm
Product Net Weight	49 g
Built-In Depth (t_2)	75 mm

© 2024 ABB. All rights reserved.

Ordering

Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	496 g
E-Number (Finland)	2312350
E-Number (Norway)	1429795
E-Number (Sweden)	2100374
E-Number (Switzerland)	467560088

Certificates and Declarations

CB Certificate	9AKK108466A3845
CCC Certificate	9AKK108466A3830
Declaration of Conformity - CE	2CCC441014D0201
Declaration of Conformity - UKCA	9AKK108467A6137
VDE Certificate	9AKK107991A9822

Installation

Instructions and Manuals	No document needed

Popular Downloads

Data Sheet, Technical Information	2CCC441003C0101

Classifications

ETIM 8	EC001546 - Push button for distribution board
ETIM 9	EC001546 - Push button for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365053
UNSPSC	39122216
eClass	V11.0 : 27142302
IDEA Granular Category Code (IGCC)	5210 >> Push button switch
Object Classification Code	S

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights → Switches, Pushbuttons and Indicator Lights, E210





© 2024 ABB. All rights reserved.