911194 ALABAMA





PVC hose with rigid PVC spiral, for suction and delivery of liquids, irrigation systems, sewage drains and cesspits.

SMOOTH SURFACES	★★★★★
FLEXIBILITY	★★★★
ABRASION RESISTANCE	★★★
TEMPERATURE RANGE	-25°C +55°C -13°F +131°F
CHEMICAL RESISTANCE	PVC table
CRUSHING RESISTANCE	★★★★

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	Ø RIGID SPIRAL (AXB IF OVAL)	SPIRAL PITCH	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm	mm	m	
2	**50,8**	58.8	4	850	220	5	15	9	3,5x7,5	10.5	50	ON DEMAND
63	**63**	71.4	4,2	1150	250	4	12	9	3,5x7,5	11	50	ON DEMAND
3	**76,2**	85.2	4,5	1450	330	4	12	9	4x8,5	13	30	ON DEMAND
80	**80**	89.6	4,8	1600	350	4	12	9	4,4x9	14.5	30	ON DEMAND
90	**90**	100	5	2000	400	3	9	9	4,5x10,3	14.5	30	ON DEMAND
4	**101,6**	111.6	5	2200	430	3	9	9	4,6x10,4	14.5	30	ON DEMAND
110	**110**	121.4	5,7	2700	480	2,5	7.5	9	4,7x10,5	15.5	20	ON DEMAND
5	**127**	139	6	3200	550	2,5	7.5	9	5,5x10,5	17.5	20	ON DEMAND
6	**152,4**	166.4	7	4300	700	2	6	9	6,5x12,3	21.5	-	ON DEMAND
8	**203,2**	223.2	10	8500	900	1,5	4.5	9	10x14,2	22.5	-	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.