Date: 11/04/2023

LH-10 ; 0 ... 4 mH2O; 4...20 mA, 2-W

Level Probe Model LH-10

Item number:	48769793	
Quantity:	1 pcs.	
Order code:	LH-10-A-YBB-GD-KK-ZZZ	W101-ZZKZZZ-F2D-GSE5
Overview:	LH-10 ; 0 ... 4 mH2O; 4...20 mA, 2-W @ 10 ... 30 V DC; Accuracy: 0.25% of span (with pressure ranges < 250 mbar: 0.5% of span) G1/2B FEP cable Cable length: 15 m UB=BN, 0V=GN Accessories cable: cable straining clamp Specifications according to data sheet: PE 81.09	
Details:	Level Probe Model LH-10 High performance version Specifications according to data sheet: PE 81.09 Accuracy: 0.25% of span (with pressure ranges < 250 mbar: 0.5% of span) Permissible medium temperature: -10...+50°C (+14...+122°F); with FEP cable -10...+85°C (+14...+185°F) Ingress protection: IP 68 Special protection: Longitudinal water resistance Output signal: 4 ... 20 mA, 2-wire Measuring range: 0 ... 4 mH2O Process connection: G 1/2 B Special design features: FEP cable Cable length: 15 m WIKA standard Accessories cable: cable straining clamp Power supply: 10 ... 30 V DC Pin assignment: UB=BN, 0V=GN *Made in Germany* on label WIKA standard - specification according to data sheet	

© 2023 - WIKA Instruments s.a.r.l.